

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	01 Hour 26 Min 37 Sec
Total Counter :	274322	Total Running Time :	2867 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.18	kN	No		
HEP :	25.0 %	32.87	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.82	kN	Yes 15	Times	
Ref :		26.30	kN			
LCP :	2.0 %	25.77	kN	Yes 15	Times	
LEP :	25.0 %	19.72	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.95	kN	Min :	3.40	kN	Punch NO.;	5
		5.60	%	Max :	4.38	kN	Punch NO.;	4
Mean Main Pressure :	SD :	26.96	kN	Min :	22.06	kN	Punch NO.;	44
		5.80	%	Max :	31.12	kN	Punch NO.;	34
Filling Depth :	Increase ;	62	Times	Decrease ;	51	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.90	mm
Filling Depth :	4.28	mm	Current Cam :	Cam B	
Main Air pressure :	0.744	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.38	kN	Max Punch ;	66
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.56	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	274322	Tablets			
A.W.C Counter :	238359	Tablets			
HEP :	144 (0.1%)	Tablets	LEP :	39 (0.0%)	Tablets
GOOD :	238176 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	01 Hour 26 Min 37 Sec
Total Counter :	274322	Total Running Time :	2867 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.95	kN	No		
HEP :	25.0 %	34.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.21	kN	Yes 15	Times	
Ref :		27.65	kN			
LCP :	2.0 %	27.10	kN	Yes 15	Times	
LEP :	25.0 %	20.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.36	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.97	kN	Min :	3.58	kN	Punch NO.;	15
		5.00	%	Max :	4.46	kN	Punch NO.;	26
Mean Main Pressure :		27.53	kN	Min :	22.33	kN	Punch NO.;	44
	SD :	5.60	%	Max :	30.37	kN	Punch NO.;	6
Filling Depth :	Increase ;	35	Times	Decrease ;	26	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.744	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.35	kN	Max Punch ;	19
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.56	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	274322	Tablets			
A.W.C Counter :	238359	Tablets			
HEP :	144 (0.1%)	Tablets	LEP :	39 (0.0%)	Tablets
GOOD :	238176 (99.9%)	Tablets			