

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 23 Sec
Total Counter :	424450	Total Running Time :	2867 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.61	kN	No		
HEP :	25.0 %	33.28	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.16	kN	Yes 15	Times	
Ref :		26.62	kN			
LCP :	2.0 %	26.09	kN	Yes 15	Times	
LEP :	25.0 %	19.97	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.90	kN	Min :	3.52	kN	Punch NO.;	71
		4.30	%	Max :	4.43	kN	Punch NO.;	75
Mean Main Pressure :		26.41	kN	Min :	21.91	kN	Punch NO.;	44
	SD :	5.50	%	Max :	29.99	kN	Punch NO.;	37
Filling Depth :	Increase ;	81	Times	Decrease ;	81	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.90	mm
Filling Depth :	4.10	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.33	kN	Max Punch ;	68
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.53	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	424450	Tablets			
A.W.C Counter :	387554	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	54 (0.0%)	Tablets
GOOD :	387341 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 23 Sec
Total Counter :	424450	Total Running Time :	2867 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.95	kN	No		
HEP :	25.0 %	34.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.21	kN	Yes 15	Times	
Ref :		27.65	kN			
LCP :	2.0 %	27.10	kN	Yes 15	Times	
LEP :	25.0 %	20.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.36	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.88	kN	Min :	3.47	kN	Punch NO.;	76
		4.30	%	Max :	4.31	kN	Punch NO.;	72
Mean Main Pressure :		27.23	kN	Min :	23.22	kN	Punch NO.;	44
	SD :	5.10	%	Max :	30.48	kN	Punch NO.;	6
Filling Depth :	Increase ;	42	Times	Decrease ;	33	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.33	kN	Max Punch ;	68
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.51	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	424450	Tablets			
A.W.C Counter :	387631	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	54 (0.0%)	Tablets
GOOD :	387418 (99.9%)	Tablets			