

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	04 Hour 04 Min 42 Sec
Total Counter :	824672	Total Running Time :	2869 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.61	kN	No		
HEP :	25.0 %	33.28	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.16	kN	Yes 15	Times	
Ref :		26.62	kN			
LCP :	2.0 %	26.09	kN	Yes 15	Times	
LEP :	25.0 %	19.97	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.92	kN	Min :	3.56	kN	Punch NO.;	36
		5.00	%	Max :	4.41	kN	Punch NO.;	66
Mean Main Pressure :		26.65	kN	Min :	21.67	kN	Punch NO.;	44
	SD :	6.20	%	Max :	30.97	kN	Punch NO.;	42
Filling Depth :	Increase ;	135	Times	Decrease ;	144	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.90	mm
Filling Depth :	3.94	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.18	kN	Max Punch ;	3
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.48	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	824672	Tablets			
A.W.C Counter :	785492	Tablets			
HEP :	243 (0.0%)	Tablets	LEP :	173 (0.0%)	Tablets
GOOD :	785076 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	04 Hour 04 Min 42 Sec
Total Counter :	824672	Total Running Time :	2869 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.95	kN	No		
HEP :	25.0 %	34.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.21	kN	Yes 15	Times	
Ref :		27.65	kN			
LCP :	2.0 %	27.10	kN	Yes 15	Times	
LEP :	25.0 %	20.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.36	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.99	kN	Min :	3.62	kN	Punch NO.;	5
SD :	3.80	%	Max :	4.41	kN	Punch NO.;	77
Mean Main Pressure :	28.30	kN	Min :	24.66	kN	Punch NO.;	44
SD :	4.40	%	Max :	31.67	kN	Punch NO.;	23
Filling Depth :	Increase ; 65	Times	Decrease ; 60	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.81	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.18	kN	Max Punch ;	3
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.50	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	824672	Tablets			
A.W.C Counter :	785492	Tablets			
HEP :	243 (0.0%)	Tablets	LEP :	173 (0.0%)	Tablets
GOOD :	785076 (99.9%)	Tablets			