

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	07 Hour 04 Min 14 Sec
Total Counter :	1375080	Total Running Time :	2872 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.59	kN	No		
HEP :	25.0 %	39.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.85	kN	Yes 15	Times	
Ref :		31.22	kN			
LCP :	2.0 %	30.60	kN	Yes 15	Times	
LEP :	25.0 %	23.42	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.88	kN	Min :	3.44	kN	Punch NO.;	5
SD :	4.50	%	Max :	4.29	kN	Punch NO.;	14
Mean Main Pressure :	30.02	kN	Min :	23.43	kN	Punch NO.;	44
SD :	5.20	%	Max :	33.47	kN	Punch NO.;	34
Filling Depth :	Increase ; 181	Times	Decrease ;	190	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.44	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.790	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.18	kN	Max Punch ;	53
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.48	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1375080	Tablets			
A.W.C Counter :	1335395	Tablets			
HEP :	254 (0.0%)	Tablets	LEP :	227 (0.0%)	Tablets
GOOD :	1334914 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509740
Print Interval :	50000 Tablets	Running Time :	07 Hour 04 Min 14 Sec
Total Counter :	1375080	Total Running Time :	2872 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.60	kN	No		
HEP :	25.0 %	38.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.07	kN	Yes 15	Times	
Ref :		30.46	kN			
LCP :	2.0 %	29.86	kN	Yes 15	Times	
LEP :	25.0 %	22.85	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.33	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.12	kN	Min :	3.75	kN	Punch NO.;	5
SD :	3.70	%	Max :	4.49	kN	Punch NO.;	64
Mean Main Pressure :	30.61	kN	Min :	24.16	kN	Punch NO.;	44
SD :	4.40	%	Max :	34.06	kN	Punch NO.;	26
Filling Depth :	Increase ; 78	Times	Decrease ;	80	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.17	mm	Pre Thickness ;	1.17	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.81	mm
Filling Depth :	4.84	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.790	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.18	kN	Max Punch ;	53
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.47	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1375080	Tablets			
A.W.C Counter :	1335395	Tablets			
HEP :	254 (0.0%)	Tablets	LEP :	227 (0.0%)	Tablets
GOOD :	1334914 (100.0%)	Tablets			