

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	02 Hour 47 Min 49 Sec
Total Counter :	564764	Total Running Time :	2882 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.49	kN	No		
HEP :	25.0 %	38.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.77	kN	Yes 15	Times	
Ref :		31.15	kN			
LCP :	2.0 %	30.52	kN	Yes 15	Times	
LEP :	25.0 %	23.36	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.83	kN	Min :	3.44	kN	Punch NO.;	5
SD :	4.00	%	Max :	4.29	kN	Punch NO.;	14
Mean Main Pressure :	31.01	kN	Min :	27.31	kN	Punch NO.;	44
SD :	4.00	%	Max :	33.86	kN	Punch NO.;	69
Filling Depth :	Increase ; 19	Times	Decrease ; 24	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.81	mm
Filling Depth :	3.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.21	kN	Max Punch ;	60
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.55	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	564764	Tablets			
A.W.C Counter :	560191	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	118 (0.0%)	Tablets
GOOD :	560058 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	02 Hour 47 Min 49 Sec
Total Counter :	564764	Total Running Time :	2882 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	36.29	kN	No		
HEP :	25.0 %	34.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.47	kN	Yes 15	Times	
Ref :		27.91	kN			
LCP :	2.0 %	27.36	kN	Yes 15	Times	
LEP :	25.0 %	20.94	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.54	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.82	kN	Min :	3.34	kN	Punch NO.;	5
SD :	4.80	%	Max :	4.26	kN	Punch NO.;	14
Mean Main Pressure :	28.37	kN	Min :	23.11	kN	Punch NO.;	44
SD :	4.50	%	Max :	31.53	kN	Punch NO.;	34
Filling Depth :	Increase ; 18	Times	Decrease ; 20	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.22	mm	Pre Thickness ;	1.22	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.89	mm	Main Thickness ;	0.89	mm
Filling Depth :	3.68	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.794	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	74
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.55	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	564764	Tablets			
A.W.C Counter :	560191	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	118 (0.0%)	Tablets
GOOD :	560058 (100.0%)	Tablets			