

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ka96535	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	05 Hour 01 Min 11 Sec
Total Counter :	1015004	Total Running Time :	2885 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	42.83	kN	No		
HEP :	25.0 %	41.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	33.60	kN	Yes 15	Times	
Ref :		32.95	kN			
LCP :	2.0 %	32.29	kN	Yes 15	Times	
LEP :	25.0 %	24.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.35	kN	Min :	3.75	kN	Punch NO.;	19
SD :	5.60	%	Max :	5.05	kN	Punch NO.;	3
Mean Main Pressure :	32.93	kN	Min :	27.73	kN	Punch NO.;	44
SD :	5.10	%	Max :	36.69	kN	Punch NO.;	69
Filling Depth :	Increase ; 97	Times	Decrease ; 88	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.81	mm
Filling Depth :	3.38	mm	Current Cam :	Cam B	
Main Air pressure :	0.787	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.31	kN	Max Punch ;	74
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.66	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1015004	Tablets			
A.W.C Counter :	1006127	Tablets			
HEP :	65 (0.0%)	Tablets	LEP :	786 (0.1%)	Tablets
GOOD :	1005276 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	ka96535	Batch NO. :	KQM2509840
Print Interval :	50000 Tablets	Running Time :	05 Hour 01 Min 11 Sec
Total Counter :	1015004	Total Running Time :	2885 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.75	kN	No		
HEP :	25.0 %	34.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.05	kN	Yes 15	Times	
Ref :		27.50	kN			
LCP :	2.0 %	26.95	kN	Yes 15	Times	
LEP :	25.0 %	20.63	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.55	kN	Min :	3.23	kN	Punch NO.;	74
SD :	4.20	%	Max :	3.84	kN	Punch NO.;	72
Mean Main Pressure :	27.27	kN	Min :	23.18	kN	Punch NO.;	44
SD :	4.70	%	Max :	30.64	kN	Punch NO.;	34
Filling Depth :	Increase ;	78	Times	Decrease ;	45	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.22	mm	Pre Thickness ;	1.22	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.81	mm
Filling Depth :	3.57	mm	Current Cam :	Cam B	
Main Air pressure :	0.787	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.31	kN	Max Punch ;	74
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.65	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1015004	Tablets			
A.W.C Counter :	1006127	Tablets			
HEP :	65 (0.0%)	Tablets	LEP :	786 (0.1%)	Tablets
GOOD :	1005276 (99.9%)	Tablets			