

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2509940
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 13 Sec
Total Counter :	62364	Total Running Time :	2893 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.96	kN	No		
HEP :	25.0 %	36.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.78	kN	Yes 15	Times	
Ref :		29.20	kN			
LCP :	2.0 %	28.61	kN	Yes 15	Times	
LEP :	25.0 %	21.90	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.44	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.03	kN	Min :	3.73	kN	Punch NO.;	8
SD :	4.20	%	Max :	4.55	kN	Punch NO.;	33
Mean Main Pressure :	29.56	kN	Min :	24.12	kN	Punch NO.;	44
SD :	5.90	%	Max :	34.94	kN	Punch NO.;	76
Filling Depth :	Increase ; 337	Times	Decrease ;	327	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.80	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.736	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	1
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.43	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	62364	Tablets			
A.W.C Counter :	58328	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	5 (0.0%)	Tablets
GOOD :	58321 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2509940
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 14 Sec
Total Counter :	62414	Total Running Time :	2893 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	36.36	kN	No		
HEP :	25.0 %	34.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.53	kN	Yes 15	Times	
Ref :		27.97	kN			
LCP :	2.0 %	27.41	kN	Yes 15	Times	
LEP :	25.0 %	20.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.00	kN	Min :	3.71	kN	Punch NO.;	3
SD :	3.40	%	Max :	4.35	kN	Punch NO.;	41
Mean Main Pressure :	28.51	kN	Min :	24.76	kN	Punch NO.;	44
SD :	4.10	%	Max :	30.95	kN	Punch NO.;	43
Filling Depth :	Increase ;	231	Times	Decrease ;	224	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.70	mm	Current Cam :	Cam B	
Main Air pressure :	0.735	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	1
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.42	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	62414	Tablets			
A.W.C Counter :	58328	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	5 (0.0%)	Tablets
GOOD :	58321 (100.0%)	Tablets			