

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509940
Print Interval :	50000 Tablets	Running Time :	14 Hour 33 Min 23 Sec
Total Counter :	2721400	Total Running Time :	2907 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.30	kN	No		
HEP :	25.0 %	38.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.62	kN	Yes 15	Times	
Ref :		31.00	kN			
LCP :	2.0 %	30.38	kN	Yes 15	Times	
LEP :	25.0 %	23.25	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.93	kN	Min :	3.44	kN	Punch NO.;	5
		3.60	%	Max :	4.35	kN	Punch NO.;	10
Mean Main Pressure :		29.66	kN	Min :	24.05	kN	Punch NO.;	44
	SD :	5.50	%	Max :	33.22	kN	Punch NO.;	50
Filling Depth :	Increase ;	720	Times	Decrease ;	686	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.80	mm	Main Thickness ;	0.80	mm
Filling Depth :	4.77	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.34	kN	Max Punch ;	76
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.39	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2721400	Tablets			
A.W.C Counter :	2713608	Tablets			
HEP :	145 (0.0%)	Tablets	LEP :	1149 (0.0%)	Tablets
GOOD :	2712314 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2509940
Print Interval :	50000 Tablets	Running Time :	14 Hour 33 Min 23 Sec
Total Counter :	2721400	Total Running Time :	2907 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.36	kN	No		
HEP :	25.0 %	33.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.96	kN	Yes 15	Times	
Ref :		26.43	kN			
LCP :	2.0 %	25.90	kN	Yes 15	Times	
LEP :	25.0 %	19.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.50	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.88	kN	Min :	3.44	kN	Punch NO.;	5
		3.80	%	Max :	4.24	kN	Punch NO.;	40
Mean Main Pressure :		25.94	kN	Min :	20.75	kN	Punch NO.;	44
	SD :	5.40	%	Max :	28.48	kN	Punch NO.;	10
Filling Depth :	Increase ;	313	Times	Decrease ;	300	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.92	mm	Main Thickness ;	0.93	mm
Filling Depth :	4.42	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.31	kN	Max Punch ;	76
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.39	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2721400	Tablets			
A.W.C Counter :	2713608	Tablets			
HEP :	145 (0.0%)	Tablets	LEP :	1149 (0.0%)	Tablets
GOOD :	2712314 (100.0%)	Tablets			