

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 13 Sec
Total Counter :	200150	Total Running Time :	2908 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.61	kN	No		
HEP :	25.0 %	36.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.51	kN	Yes 15	Times	
Ref :		28.93	kN			
LCP :	2.0 %	28.35	kN	Yes 15	Times	
LEP :	25.0 %	21.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.88	kN	Min :	3.38	kN	Punch NO.;	15
		5.70	%	Max :	4.33	kN	Punch NO.;	54
Mean Main Pressure :		28.95	kN	Min :	23.60	kN	Punch NO.;	57
	SD :	7.10	%	Max :	34.12	kN	Punch NO.;	76
Filling Depth :	Increase ;	797	Times	Decrease ;	776	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.80	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.33	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.30	kN	Max Punch ;	74
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.62	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200150	Tablets			
A.W.C Counter :	196003	Tablets			
HEP :	35 (0.0%)	Tablets	LEP :	231 (0.1%)	Tablets
GOOD :	195737 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : rp98927 Print Interval : 50000 Tablets Total Counter : 200150 Station : Station 2	Product Name : Panto 40 mg STKQ1B00 Batch NO. : KQM2510040 Running Time : 00 Hour 59 Min 13 Sec Total Running Time : 2908 Hour 56 Min
--	--

Setting Value

Feeder :	Auto ;	43	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.53	kN	No		
HEP :	25.0 %	34.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.88	kN	Yes 15	Times	
Ref :		27.33	kN			
LCP :	2.0 %	26.79	kN	Yes 15	Times	
LEP :	25.0 %	20.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.85	kN	Min :	3.51	kN	Punch NO.;	50
		5.10	%	Max :	4.50	kN	Punch NO.;	56
Mean Main Pressure :		27.40	kN	Min :	23.77	kN	Punch NO.;	44
	SD :	5.20	%	Max :	30.93	kN	Punch NO.;	5
Filling Depth :	Increase ;	323	Times	Decrease ;	322	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.70	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.30	kN	Max Punch ;	74
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.62	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200150	Tablets			
A.W.C Counter :	196003	Tablets			
HEP :	35 (0.0%)	Tablets	LEP :	231 (0.1%)	Tablets
GOOD :	195737 (99.9%)	Tablets			