

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pn98247	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	01 Hour 57 Min 53 Sec
Total Counter :	398458	Total Running Time :	2909 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.62	kN	No		
HEP :	25.0 %	37.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.30	kN	Yes 15	Times	
Ref :		29.70	kN			
LCP :	2.0 %	29.11	kN	Yes 15	Times	
LEP :	25.0 %	22.28	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.79	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.01	kN	Min :	3.32	kN	Punch NO.;	18
SD :	5.80	%	Max :	4.68	kN	Punch NO.;	45
Mean Main Pressure :	30.23	kN	Min :	23.25	kN	Punch NO.;	44
SD :	7.00	%	Max :	35.46	kN	Punch NO.;	7
Filling Depth :	Increase ; 20	Times	Decrease ;	16	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.82	mm
Filling Depth :	3.42	mm	Current Cam :	Cam B	
Main Air pressure :	0.785	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.37	kN	Max Punch ;	66
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.65	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	398458	Tablets			
A.W.C Counter :	392494	Tablets			
HEP :	77 (0.0%)	Tablets	LEP :	558 (0.1%)	Tablets
GOOD :	391859 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pn98247	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	01 Hour 57 Min 54 Sec
Total Counter :	398512	Total Running Time :	2909 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.53	kN	No		
HEP :	25.0 %	34.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.88	kN	Yes 15	Times	
Ref :		27.33	kN			
LCP :	2.0 %	26.79	kN	Yes 15	Times	
LEP :	25.0 %	20.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.82	kN	Min :	3.31	kN	Punch NO.;	5
SD :	5.50	%	Max :	4.48	kN	Punch NO.;	41
Mean Main Pressure :	27.67	kN	Min :	24.33	kN	Punch NO.;	44
SD :	5.60	%	Max :	30.95	kN	Punch NO.;	34
Filling Depth :	Increase ; 13	Times	Decrease ; 12	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.782	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.35	kN	Max Punch ;	26
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.65	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	398512	Tablets			
A.W.C Counter :	392494	Tablets			
HEP :	77 (0.0%)	Tablets	LEP :	558 (0.1%)	Tablets
GOOD :	391859 (99.8%)	Tablets			