

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pn98247	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	02 Hour 27 Min 47 Sec
Total Counter :	499554	Total Running Time :	2910 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.62	kN	No		
HEP :	25.0 %	37.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.30	kN	Yes 15	Times	
Ref :		29.70	kN			
LCP :	2.0 %	29.11	kN	Yes 15	Times	
LEP :	25.0 %	22.28	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.79	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.97	kN	Min :	3.44	kN	Punch NO.;	5
		5.60	%	Max :	4.88	kN	Punch NO.;	75
Mean Main Pressure :		29.42	kN	Min :	22.94	kN	Punch NO.;	57
	SD :	6.90	%	Max :	34.13	kN	Punch NO.;	7
Filling Depth :	Increase ;	43	Times	Decrease ;	40	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.82	mm
Filling Depth :	3.39	mm	Current Cam :	Cam B	
Main Air pressure :	0.795	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	36	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.39	kN	Max Punch ;	74
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.58	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	499554	Tablets			
A.W.C Counter :	493518	Tablets			
HEP :	91 (0.0%)	Tablets	LEP :	774 (0.2%)	Tablets
GOOD :	492653 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	pn98247	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	02 Hour 27 Min 47 Sec
Total Counter :	499554	Total Running Time :	2910 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.97	kN	No		
HEP :	25.0 %	34.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.23	kN	Yes 15	Times	
Ref :		27.67	kN			
LCP :	2.0 %	27.12	kN	Yes 15	Times	
LEP :	25.0 %	20.75	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.37	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.85	kN	Min :	2.35	kN	Punch NO.;	75
		7.00	%	Max :	4.42	kN	Punch NO.;	48
Mean Main Pressure :		28.08	kN	Min :	20.40	kN	Punch NO.;	44
	SD :	5.80	%	Max :	31.55	kN	Punch NO.;	10
Filling Depth :	Increase ;	24	Times	Decrease ;	24	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.87	mm
Filling Depth :	3.63	mm	Current Cam :	Cam B	
Main Air pressure :	0.795	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	36	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.38	kN	Max Punch ;	30
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.58	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	499554	Tablets			
A.W.C Counter :	493518	Tablets			
HEP :	91 (0.0%)	Tablets	LEP :	774 (0.2%)	Tablets
GOOD :	492653 (99.8%)	Tablets			