

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	am98755	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	10 Hour 31 Min 17 Sec
Total Counter :	2132140	Total Running Time :	2918 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.30	kN	No		
HEP :	25.0 %	35.86	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.26	kN	Yes 15	Times	
Ref :		28.69	kN			
LCP :	2.0 %	28.12	kN	Yes 15	Times	
LEP :	25.0 %	21.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.01	kN	Min :	3.60	kN	Punch NO.;	59
SD :	5.50	%	Max :	4.78	kN	Punch NO.;	30
Mean Main Pressure :	27.96	kN	Min :	21.29	kN	Punch NO.;	44
SD :	7.00	%	Max :	31.87	kN	Punch NO.;	26
Filling Depth :	Increase ; 63	Times	Decrease ;	58	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.81	mm	Main Thickness ;	0.82	mm
Filling Depth :	3.43	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.733	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.34	kN	Max Punch ;	67
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.45	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2132140	Tablets			
A.W.C Counter :	2118615	Tablets			
HEP :	450 (0.0%)	Tablets	LEP :	2325 (0.1%)	Tablets
GOOD :	2115840 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 40 mg STKQ1B00
User ID :	am98755	Batch NO. :	KQM2510040
Print Interval :	50000 Tablets	Running Time :	10 Hour 31 Min 17 Sec
Total Counter :	2132140	Total Running Time :	2918 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	25	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.92	kN	No		
HEP :	25.0 %	33.58	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.40	kN	Yes 15	Times	
Ref :		26.86	kN			
LCP :	2.0 %	26.33	kN	Yes 15	Times	
LEP :	25.0 %	20.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.97	kN	Min :	3.52	kN	Punch NO.;	5
		5.00	%	Max :	4.53	kN	Punch NO.;	72
Mean Main Pressure :		26.87	kN	Min :	21.07	kN	Punch NO.;	57
	SD :	6.10	%	Max :	31.28	kN	Punch NO.;	34
Filling Depth :	Increase ;	26	Times	Decrease ;	23	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.87	mm
Filling Depth :	3.72	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.733	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.35	kN	Max Punch ;	62
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.45	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2132140	Tablets			
A.W.C Counter :	2118615	Tablets			
HEP :	450 (0.0%)	Tablets	LEP :	2325 (0.1%)	Tablets
GOOD :	2115840 (99.9%)	Tablets			