

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | Allo 200mg STUB3D00   |
| User ID :        | pb97604       | Batch NO. :          | UBM2500420            |
| Print Interval : | 50000 Tablets | Running Time :       | 15 Hour 23 Min 48 Sec |
| Total Counter :  | 250098        | Total Running Time : | 2923 Hour 21 Min      |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 141      | %       | Manual ;           | 23           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 1500000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 20       | Min     | Supply Time ;      | 2.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 1        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 18.37    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 17.66    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.5 %       | 14.48    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 14.13    | kN      |                    |              |           |
| LCP :                              | 2.5 %       | 13.78    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 10.60    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 9.89     | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |               |       |               |       |    |            |    |
|----------------------|---------------|-------|---------------|-------|----|------------|----|
| Mean Pre Pressure :  | 2.19          | kN    | Min :         | 2.18  | kN | Punch NO.; | 18 |
| SD :                 | 0.40          | %     | Max :         | 2.22  | kN | Punch NO.; | 10 |
| Mean Main Pressure : | 14.05         | kN    | Min :         | 12.47 | kN | Punch NO.; | 11 |
| SD :                 | 6.30          | %     | Max :         | 16.08 | kN | Punch NO.; | 45 |
| Filling Depth :      | Increase ; 85 | Times | Decrease ; 86 | Times |    |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 28       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.50    | mm  | Pre Thickness ;  | 4.50     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.27    | mm  | Main Thickness ; | 3.27     | mm           |
| Filling Depth :               | 8.24    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.814   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 18      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 12      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.16 | kN |             |    |
|                  | Max ;     | 0.21 | kN | Max Punch ; | 41 |
| Lower Punch :    | Average ; | 0.12 | kN |             |    |
|                  | Max ;     | 0.17 | kN | Max Punch ; | 49 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 250098            | Tablets |       |            |         |
| A.W.C Counter : | 239264            | Tablets |       |            |         |
| HEP :           | 609 (0.3%)        | Tablets | LEP : | 102 (0.0%) | Tablets |
| GOOD :          | 238553<br>(99.7%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | Allo 200mg STUB3D00   |
| User ID :        | pb97604       | Batch NO. :          | UBM2500420            |
| Print Interval : | 50000 Tablets | Running Time :       | 15 Hour 23 Min 48 Sec |
| Total Counter :  | 250098        | Total Running Time : | 2923 Hour 21 Min      |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 113       | %       | Manual ;           | 25           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 1500000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 20        | Min     | Supply Time ;      | 2.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 20        | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 18.48     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 17.77     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.5 %  | 14.57     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 14.22     | kN      |                    |              |           |
| LCP :                              | 2.5 %  | 13.86     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 10.66     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 9.95      | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 1      | Rotations |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.19       | kN  | Min : | 2.18       | kN  | Punch NO.; | 15 |
| SD :                 | 0.60       | %   | Max : | 2.24       | kN  | Punch NO.; | 3  |
| Mean Main Pressure : | 14.20      | kN  | Min : | 12.96      | kN  | Punch NO.; | 51 |
| SD :                 | 4.40       | %   | Max : | 15.93      | kN  | Punch NO.; | 3  |
| Filling Depth :      | Increase ; | 133 | Times | Decrease ; | 114 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 23       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.50    | mm  | Pre Thickness ;  | 4.50     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.50    | mm  | Main Thickness ; | 3.50     | mm           |
| Filling Depth :               | 9.04    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.814   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 18      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 12      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.16 | kN |             |    |
|                  | Max ;     | 0.21 | kN | Max Punch ; | 41 |
| Lower Punch :    | Average ; | 0.12 | kN |             |    |
|                  | Max ;     | 0.18 | kN | Max Punch ; | 49 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 250098            | Tablets |       |            |         |
| A.W.C Counter : | 239264            | Tablets |       |            |         |
| HEP :           | 609 (0.3%)        | Tablets | LEP : | 102 (0.0%) | Tablets |
| GOOD :          | 238553<br>(99.7%) | Tablets |       |            |         |