

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	rp98927	Batch NO. :	UBM2500420
Print Interval :	50000 Tablets	Running Time :	23 Hour 15 Min 49 Sec
Total Counter :	1200422	Total Running Time :	2931 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	163	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	20.49	kN	No		
HEP :	25.0 %	19.70	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	16.16	kN	Yes 15	Times	
Ref :		15.76	kN			
LCP :	2.5 %	15.37	kN	Yes 15	Times	
LEP :	25.0 %	11.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.03	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.18	kN	Min :	2.16	kN	Punch NO.;	29
SD :	0.40	%	Max :	2.21	kN	Punch NO.;	51
Mean Main Pressure :	15.49	kN	Min :	13.04	kN	Punch NO.;	51
SD :	7.90	%	Max :	18.56	kN	Punch NO.;	41
Filling Depth :	Increase ; 200	Times	Decrease ;	229	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.27	mm	Main Thickness ;	3.27	mm
Filling Depth :	8.37	mm	Current Cam :	Cam C	
Main Air pressure :	0.740	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	41
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1200422	Tablets			
A.W.C Counter :	1186366	Tablets			
HEP :	698 (0.1%)	Tablets	LEP :	166 (0.0%)	Tablets
GOOD :	1185502 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	rp98927	Batch NO. :	UBM2500420
Print Interval :	50000 Tablets	Running Time :	23 Hour 15 Min 49 Sec
Total Counter :	1200422	Total Running Time :	2931 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	152	%	Manual ;	25	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	19.75	kN	No		
HEP :	25.0 %	18.99	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	15.57	kN	Yes 15	Times	
Ref :		15.19	kN			
LCP :	2.5 %	14.81	kN	Yes 15	Times	
LEP :	25.0 %	11.39	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.63	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.13	kN	Min :	2.11	kN	Punch NO.;	28
SD :	0.40	%	Max :	2.15	kN	Punch NO.;	1
Mean Main Pressure :	14.84	kN	Min :	13.20	kN	Punch NO.;	11
SD :	5.00	%	Max :	16.72	kN	Punch NO.;	40
Filling Depth :	Increase ;	435	Times	Decrease ;	406	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	8.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.740	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	30
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1200422	Tablets			
A.W.C Counter :	1186366	Tablets			
HEP :	698 (0.1%)	Tablets	LEP :	166 (0.0%)	Tablets
GOOD :	1185502 (99.9%)	Tablets			