

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	pb97604	Batch NO. :	UBM2500520
Print Interval :	50000 Tablets	Running Time :	02 Hour 29 Min 50 Sec
Total Counter :	300144	Total Running Time :	2936 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	21.34	kN	No		
HEP :	25.0 %	20.52	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	16.83	kN	Yes 15	Times	
Ref :		16.42	kN			
LCP :	2.5 %	16.01	kN	Yes 15	Times	
LEP :	25.0 %	12.31	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.17	kN	Min :	2.15	kN	Punch NO.;	36
		0.40	%	Max :	2.20	kN	Punch NO.;	15
Mean Main Pressure :		16.15	kN	Min :	14.70	kN	Punch NO.;	43
	SD :	4.70	%	Max :	18.02	kN	Punch NO.;	14
Filling Depth :	Increase ;	428	Times	Decrease ;	407	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	34	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.27	mm	Main Thickness ;	3.27	mm
Filling Depth :	9.07	mm	Current Cam :	Cam C	
Main Air pressure :	0.697	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.27	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300144	Tablets			
A.W.C Counter :	291600	Tablets			
HEP :	844 (0.3%)	Tablets	LEP :	191 (0.1%)	Tablets
GOOD :	290565 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo 200mg STUB3D00
User ID :	pb97604	Batch NO. :	UBM2500520
Print Interval :	50000 Tablets	Running Time :	02 Hour 29 Min 50 Sec
Total Counter :	300144	Total Running Time :	2936 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	25	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1500000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	19.03	kN	No		
HEP :	25.0 %	18.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	15.01	kN	Yes 15	Times	
Ref :		14.64	kN			
LCP :	2.5 %	14.28	kN	Yes 15	Times	
LEP :	25.0 %	10.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.15	kN	Min :	2.12	kN	Punch NO.;	19
SD :	0.70	%	Max :	2.19	kN	Punch NO.;	10
Mean Main Pressure :	14.49	kN	Min :	12.83	kN	Punch NO.;	5
SD :	5.20	%	Max :	17.01	kN	Punch NO.;	26
Filling Depth :	Increase ;	753	Times	Decrease ;	648	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.53	mm	Main Thickness ;	3.53	mm
Filling Depth :	9.06	mm	Current Cam :	Cam C	
Main Air pressure :	0.697	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.27	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300144	Tablets			
A.W.C Counter :	291600	Tablets			
HEP :	844 (0.3%)	Tablets	LEP :	191 (0.1%)	Tablets
GOOD :	290565 (99.6%)	Tablets			