

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	02 Hour 17 Min 01 Sec
Total Counter :	450244	Total Running Time :	2948 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.10	kN	No		
HEP :	25.0 %	39.52	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	32.41	kN	Yes 15	Times	
Ref :		31.62	kN			
LCP :	2.5 %	30.83	kN	Yes 15	Times	
LEP :	25.0 %	23.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.15	kN	Min :	3.76	kN	Punch NO.;	11
SD :	4.70	%	Max :	4.67	kN	Punch NO.;	46
Mean Main Pressure :	32.39	kN	Min :	27.65	kN	Punch NO.;	52
SD :	4.10	%	Max :	34.81	kN	Punch NO.;	46
Filling Depth :	Increase ; 39	Times	Decrease ;	53	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	3.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	5
Lower Punch :	Average ;	0.43	kN		
	Max ;	1.08	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450244	Tablets			
A.W.C Counter :	434926	Tablets			
HEP :	50 (0.0%)	Tablets	LEP :	570 (0.1%)	Tablets
GOOD :	434306 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	02 Hour 17 Min 01 Sec
Total Counter :	450244	Total Running Time :	2948 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	25	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.70	kN	No		
HEP :	25.0 %	40.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	32.88	kN	Yes 15	Times	
Ref :		32.08	kN			
LCP :	2.5 %	31.28	kN	Yes 15	Times	
LEP :	25.0 %	24.06	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.04	kN	Min :	3.55	kN	Punch NO.;	52
SD :	4.90	%	Max :	4.42	kN	Punch NO.;	10
Mean Main Pressure :	31.75	kN	Min :	25.75	kN	Punch NO.;	52
SD :	4.20	%	Max :	33.86	kN	Punch NO.;	3
Filling Depth :	Increase ;	10	Times	Decrease ;	29	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.77	mm	Main Thickness ;	0.77	mm
Filling Depth :	3.79	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	5
Lower Punch :	Average ;	0.42	kN		
	Max ;	1.03	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450244	Tablets			
A.W.C Counter :	434926	Tablets			
HEP :	50 (0.0%)	Tablets	LEP :	570 (0.1%)	Tablets
GOOD :	434306 (99.9%)	Tablets			