

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	07 Hour 43 Min 56 Sec
Total Counter :	1450750	Total Running Time :	2953 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.85	kN	No		
HEP :	25.0 %	37.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.48	kN	Yes 15	Times	
Ref :		29.88	kN			
LCP :	2.0 %	29.29	kN	Yes 15	Times	
LEP :	25.0 %	22.41	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.65	kN	Min :	3.31	kN	Punch NO.;	70
		4.10	%	Max :	3.97	kN	Punch NO.;	18
Mean Main Pressure :	SD :	29.29	kN	Min :	26.07	kN	Punch NO.;	70
		3.80	%	Max :	31.17	kN	Punch NO.;	51
Filling Depth :	Increase ;	337	Times	Decrease ;	337	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	4.00	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.765	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	53
Lower Punch :	Average ;	0.36	kN		
	Max ;	0.81	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1450750	Tablets			
A.W.C Counter :	1425395	Tablets			
HEP :	137 (0.0%)	Tablets	LEP :	1274 (0.1%)	Tablets
GOOD :	1423984 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	07 Hour 43 Min 56 Sec
Total Counter :	1450750	Total Running Time :	2953 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	25	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.35	kN	No		
HEP :	25.0 %	36.88	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.09	kN	Yes 15	Times	
Ref :		29.50	kN			
LCP :	2.0 %	28.91	kN	Yes 15	Times	
LEP :	25.0 %	22.13	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.63	kN	Min :	3.32	kN	Punch NO.;	64
		4.00	%	Max :	3.95	kN	Punch NO.;	50
Mean Main Pressure :	SD :	29.57	kN	Min :	27.58	kN	Punch NO.;	77
		3.50	%	Max :	31.89	kN	Punch NO.;	48
Filling Depth :	Increase ;	112	Times	Decrease ;	119	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.75	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.70	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.765	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	21
Lower Punch :	Average ;	0.36	kN		
	Max ;	0.81	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1450750	Tablets			
A.W.C Counter :	1425472	Tablets			
HEP :	137 (0.0%)	Tablets	LEP :	1274 (0.1%)	Tablets
GOOD :	1424061 (99.9%)	Tablets			