

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	vy190186	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	12 Hour 13 Min 46 Sec
Total Counter :	2276402	Total Running Time :	2958 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.89	kN	No		
HEP :	25.0 %	37.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.51	kN	Yes 15	Times	
Ref :		29.92	kN			
LCP :	2.0 %	29.32	kN	Yes 15	Times	
LEP :	25.0 %	22.44	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.94	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.75	kN	Min :	3.44	kN	Punch NO.;	13
SD :	4.00	%	Max :	4.08	kN	Punch NO.;	42
Mean Main Pressure :	30.51	kN	Min :	27.70	kN	Punch NO.;	47
SD :	4.30	%	Max :	33.31	kN	Punch NO.;	60
Filling Depth :	Increase ; 160	Times	Decrease ; 159	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	4.15	mm	Current Cam :	Cam B	
Main Air pressure :	0.772	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	21
Lower Punch :	Average ;	0.41	kN		
	Max ;	0.84	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2276402	Tablets			
A.W.C Counter :	2238034	Tablets			
HEP :	419 (0.0%)	Tablets	LEP :	1876 (0.1%)	Tablets
GOOD :	2235739 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	vy190186	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	12 Hour 13 Min 46 Sec
Total Counter :	2276402	Total Running Time :	2958 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.75	kN	No		
HEP :	25.0 %	36.30	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.62	kN	Yes	15	Times
Ref :		29.04	kN			
LCP :	2.0 %	28.46	kN	Yes	15	Times
LEP :	25.0 %	21.78	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.33	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.67	kN	Min :	3.15	kN	Punch NO.;	24
SD :	5.30	%	Max :	4.14	kN	Punch NO.;	72
Mean Main Pressure :	29.02	kN	Min :	24.72	kN	Punch NO.;	24
SD :	4.90	%	Max :	31.95	kN	Punch NO.;	3
Filling Depth :	Increase ;	221	Times	Decrease ;	224	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.75	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.772	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	21
Lower Punch :	Average ;	0.41	kN		
	Max ;	0.86	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2276402	Tablets			
A.W.C Counter :	2238034	Tablets			
HEP :	419 (0.0%)	Tablets	LEP :	1876 (0.1%)	Tablets
GOOD :	2235739 (99.9%)	Tablets			