

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2510140
Print Interval :	50000 Tablets	Running Time :	07 Hour 21 Min 13 Sec
Total Counter :	1350898	Total Running Time :	2968 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.83	kN	No		
HEP :	25.0 %	38.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.25	kN	Yes 15	Times	
Ref :		30.64	kN			
LCP :	2.0 %	30.03	kN	Yes 15	Times	
LEP :	25.0 %	22.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.45	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.60	kN	Min :	3.36	kN	Punch NO.;	55
		3.10	%	Max :	3.85	kN	Punch NO.;	26
Mean Main Pressure :	SD :	30.62	kN	Min :	28.40	kN	Punch NO.;	59
		3.10	%	Max :	32.61	kN	Punch NO.;	68
Filling Depth :	Increase ;	65	Times	Decrease ;	74	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.88	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.22	kN	Max Punch ;	37
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.43	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1350898	Tablets			
A.W.C Counter :	1345294	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	315 (0.0%)	Tablets
GOOD :	1344971 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2510140
Print Interval :	50000 Tablets	Running Time :	07 Hour 21 Min 13 Sec
Total Counter :	1350898	Total Running Time :	2968 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	59	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.74	kN	No		
HEP :	25.0 %	37.25	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.39	kN	Yes 15	Times	
Ref :		29.80	kN			
LCP :	2.0 %	29.20	kN	Yes 15	Times	
LEP :	25.0 %	22.35	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.64	kN	Min :	3.26	kN	Punch NO.;	59
SD :	5.30	%	Max :	4.18	kN	Punch NO.;	65
Mean Main Pressure :	29.69	kN	Min :	26.33	kN	Punch NO.;	59
SD :	4.90	%	Max :	32.83	kN	Punch NO.;	65
Filling Depth :	Increase ;	113	Times	Decrease ;	112	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.75	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.48	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	17
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.43	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1350898	Tablets			
A.W.C Counter :	1345294	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	315 (0.0%)	Tablets
GOOD :	1344971 (100.0%)	Tablets			