

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	13 Hour 20 Min 27 Sec
Total Counter :	2456086	Total Running Time :	2989 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	36.40	kN	No		
HEP :	25.0 %	35.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.56	kN	Yes 15	Times	
Ref :		28.00	kN			
LCP :	2.0 %	27.44	kN	Yes 15	Times	
LEP :	25.0 %	21.00	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.60	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.72	kN	Min :	3.32	kN	Punch NO.;	9
SD :	5.10	%	Max :	4.17	kN	Punch NO.;	50
Mean Main Pressure :	27.14	kN	Min :	23.48	kN	Punch NO.;	9
SD :	5.10	%	Max :	30.40	kN	Punch NO.;	65
Filling Depth :	Increase ;	356	Times	Decrease ;	247	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.99	mm
Filling Depth :	4.13	mm	Current Cam :	Cam B	
Main Air pressure :	0.744	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	29
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.51	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2456086	Tablets			
A.W.C Counter :	2443155	Tablets			
HEP :	354 (0.0%)	Tablets	LEP :	654 (0.0%)	Tablets
GOOD :	2442147 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	13 Hour 20 Min 27 Sec
Total Counter :	2456086	Total Running Time :	2989 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.51	kN	No		
HEP :	25.0 %	33.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.07	kN	Yes 15	Times	
Ref :		26.54	kN			
LCP :	2.0 %	26.01	kN	Yes 15	Times	
LEP :	25.0 %	19.91	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.66	kN	Min :	3.30	kN	Punch NO.;	37
SD :	5.20	%	Max :	4.17	kN	Punch NO.;	52
Mean Main Pressure :	26.40	kN	Min :	23.55	kN	Punch NO.;	9
SD :	4.70	%	Max :	29.46	kN	Punch NO.;	52
Filling Depth :	Increase ;	817	Times	Decrease ;	803	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.74	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.94	mm
Filling Depth :	3.61	mm	Current Cam :	Cam B	
Main Air pressure :	0.744	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	11
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.51	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2456086	Tablets			
A.W.C Counter :	2443155	Tablets			
HEP :	354 (0.0%)	Tablets	LEP :	654 (0.0%)	Tablets
GOOD :	2442147 (100.0%)	Tablets			