

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	yd98913	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	00 Hour 16 Min 11 Sec
Total Counter :	48374	Total Running Time :	2990 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	76	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.94	kN	No		
HEP :	25.0 %	34.56	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.20	kN	Yes 15	Times	
Ref :		27.65	kN			
LCP :	2.0 %	27.09	kN	Yes 15	Times	
LEP :	25.0 %	20.73	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.71	kN	Min :	3.28	kN	Punch NO.;	60
		5.80	%	Max :	4.29	kN	Punch NO.;	24
Mean Main Pressure :	SD :	28.33	kN	Min :	24.81	kN	Punch NO.;	60
		4.80	%	Max :	32.00	kN	Punch NO.;	24
Filling Depth :	Increase ;	38	Times	Decrease ;	18	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.69	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.39	kN		
	Max ;	0.55	kN	Max Punch ;	63
Lower Punch :	Average ;	0.44	kN		
	Max ;	1.04	kN	Max Punch ;	72
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	48374	Tablets			
A.W.C Counter :	40831	Tablets			
HEP :	43 (0.1%)	Tablets	LEP :	31 (0.1%)	Tablets
GOOD :	40757 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	yd98913	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	00 Hour 16 Min 11 Sec
Total Counter :	48374	Total Running Time :	2990 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.17	kN	No		
HEP :	25.0 %	36.70	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.95	kN	Yes	15	Times
Ref :		29.36	kN			
LCP :	2.0 %	28.77	kN	Yes	15	Times
LEP :	25.0 %	22.02	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.55	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.09	kN	Min :	3.72	kN	Punch NO.;	25
SD :	3.90	%	Max :	4.70	kN	Punch NO.;	38
Mean Main Pressure :	29.42	kN	Min :	27.67	kN	Punch NO.;	12
SD :	2.90	%	Max :	32.12	kN	Punch NO.;	38
Filling Depth :	Increase ;	8	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.25	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.39	kN		
	Max ;	0.55	kN	Max Punch ;	63
Lower Punch :	Average ;	0.44	kN		
	Max ;	0.95	kN	Max Punch ;	60
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	48374	Tablets			
A.W.C Counter :	40831	Tablets			
HEP :	43 (0.1%)	Tablets	LEP :	31 (0.1%)	Tablets
GOOD :	40757 (99.8%)	Tablets			