

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 11 Sec
Total Counter :	100020	Total Running Time :	2991 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.25	kN	No		
HEP :	25.0 %	39.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	32.36	kN	Yes 15	Times	
Ref :		31.73	kN			
LCP :	2.0 %	31.09	kN	Yes 15	Times	
LEP :	25.0 %	23.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.21	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.38	kN	Min :	3.94	kN	Punch NO.;	14
SD :	5.60	%	Max :	5.07	kN	Punch NO.;	46
Mean Main Pressure :	33.36	kN	Min :	30.72	kN	Punch NO.;	76
SD :	4.00	%	Max :	36.90	kN	Punch NO.;	43
Filling Depth :	Increase ; 90	Times	Decrease ; 32	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	4.59	mm	Current Cam :	Cam B	
Main Air pressure :	0.760	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.24	kN	Max Punch ;	65
Lower Punch :	Average ;	0.43	kN		
	Max ;	1.26	kN	Max Punch ;	72
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100020	Tablets			
A.W.C Counter :	87094	Tablets			
HEP :	47 (0.1%)	Tablets	LEP :	211 (0.2%)	Tablets
GOOD :	86836 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 11 Sec
Total Counter :	100020	Total Running Time :	2991 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.17	kN	No		
HEP :	25.0 %	36.70	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.95	kN	Yes 15	Times	
Ref :		29.36	kN			
LCP :	2.0 %	28.77	kN	Yes 15	Times	
LEP :	25.0 %	22.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.55	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.02	kN	Min :	3.61	kN	Punch NO.;	14
SD :	4.30	%	Max :	4.34	kN	Punch NO.;	19
Mean Main Pressure :	29.42	kN	Min :	27.25	kN	Punch NO.;	14
SD :	3.70	%	Max :	31.59	kN	Punch NO.;	19
Filling Depth :	Increase ;	17	Times	Decrease ;	20	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.31	mm	Current Cam :	Cam B	
Main Air pressure :	0.760	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.23	kN	Max Punch ;	61
Lower Punch :	Average ;	0.43	kN		
	Max ;	1.26	kN	Max Punch ;	72
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100020	Tablets			
A.W.C Counter :	87094	Tablets			
HEP :	47 (0.1%)	Tablets	LEP :	211 (0.2%)	Tablets
GOOD :	86836 (99.7%)	Tablets			