

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	04 Hour 38 Min 20 Sec
Total Counter :	850408	Total Running Time :	2995 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	44.46	kN	No		
HEP :	25.0 %	42.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.89	kN	Yes 15	Times	
Ref :		34.20	kN			
LCP :	2.0 %	33.52	kN	Yes 15	Times	
LEP :	25.0 %	25.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.94	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.93	kN	Min :	3.37	kN	Punch NO.;	75
SD :	6.80	%	Max :	4.74	kN	Punch NO.;	46
Mean Main Pressure :	34.52	kN	Min :	30.49	kN	Punch NO.;	74
SD :	5.10	%	Max :	37.95	kN	Punch NO.;	19
Filling Depth :	Increase ; 327	Times	Decrease ;	317	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.52	mm	Main Thickness ;	0.82	mm
Filling Depth :	4.36	mm	Current Cam :	Cam B	
Main Air pressure :	0.740	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.27	kN	Max Punch ;	39
Lower Punch :	Average ;	0.50	kN		
	Max ;	1.25	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	850408	Tablets			
A.W.C Counter :	831048	Tablets			
HEP :	87 (0.0%)	Tablets	LEP :	275 (0.0%)	Tablets
GOOD :	830686 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	04 Hour 38 Min 20 Sec
Total Counter :	850408	Total Running Time :	2995 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.95	kN	No		
HEP :	25.0 %	38.41	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	31.35	kN	Yes	15	Times
Ref :		30.73	kN			
LCP :	2.0 %	30.12	kN	Yes	15	Times
LEP :	25.0 %	23.05	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	21.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.70	kN	Min :	3.40	kN	Punch NO.;	49
SD :	3.60	%	Max :	4.01	kN	Punch NO.;	64
Mean Main Pressure :	30.82	kN	Min :	28.34	kN	Punch NO.;	14
SD :	3.10	%	Max :	33.11	kN	Punch NO.;	36
Filling Depth :	Increase ;	67	Times	Decrease ;	73	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.740	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	10
Lower Punch :	Average ;	0.50	kN		
	Max ;	1.25	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	850408	Tablets			
A.W.C Counter :	831048	Tablets			
HEP :	87 (0.0%)	Tablets	LEP :	275 (0.0%)	Tablets
GOOD :	830686 (100.0%)	Tablets			