

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	05 Hour 11 Min 09 Sec
Total Counter :	950432	Total Running Time :	2995 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	71	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.97	kN	No		
HEP :	25.0 %	42.28	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.50	kN	Yes 15	Times	
Ref :		33.83	kN			
LCP :	2.0 %	33.15	kN	Yes 15	Times	
LEP :	25.0 %	25.37	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.88	kN	Min :	3.26	kN	Punch NO.;	35
SD :	8.00	%	Max :	4.74	kN	Punch NO.;	11
Mean Main Pressure :	34.26	kN	Min :	29.70	kN	Punch NO.;	35
SD :	6.20	%	Max :	39.80	kN	Punch NO.;	11
Filling Depth :	Increase ; 352	Times	Decrease ;	357	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.52	mm	Main Thickness ;	0.82	mm
Filling Depth :	4.21	mm	Current Cam :	Cam B	
Main Air pressure :	0.735	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	2
Lower Punch :	Average ;	0.45	kN		
	Max ;	0.99	kN	Max Punch ;	60
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	950432	Tablets			
A.W.C Counter :	927963	Tablets			
HEP :	88 (0.0%)	Tablets	LEP :	281 (0.0%)	Tablets
GOOD :	927594 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	05 Hour 11 Min 09 Sec
Total Counter :	950432	Total Running Time :	2995 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	42.84	kN	No		
HEP :	25.0 %	41.19	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	33.61	kN	Yes 15	Times	
Ref :		32.95	kN			
LCP :	2.0 %	32.29	kN	Yes 15	Times	
LEP :	25.0 %	24.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.07	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.89	kN	Min :	3.50	kN	Punch NO.;	74
SD :	5.90	%	Max :	4.48	kN	Punch NO.;	39
Mean Main Pressure :	32.27	kN	Min :	28.52	kN	Punch NO.;	74
SD :	4.80	%	Max :	35.45	kN	Punch NO.;	39
Filling Depth :	Increase ;	86	Times	Decrease ;	85	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.68	mm	Current Cam :	Cam B	
Main Air pressure :	0.735	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	2
Lower Punch :	Average ;	0.45	kN		
	Max ;	0.96	kN	Max Punch ;	72
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	950432	Tablets			
A.W.C Counter :	927963	Tablets			
HEP :	88 (0.0%)	Tablets	LEP :	281 (0.0%)	Tablets
GOOD :	927594 (100.0%)	Tablets			