

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	06 Hour 00 Min 21 Sec
Total Counter :	1100524	Total Running Time :	2996 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	71	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	42.16	kN	No		
HEP :	25.0 %	40.54	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	33.08	kN	Yes 15	Times	
Ref :		32.43	kN			
LCP :	2.0 %	31.78	kN	Yes 15	Times	
LEP :	25.0 %	24.33	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.70	kN	Min :	3.17	kN	Punch NO.;	28
SD :	6.00	%	Max :	4.16	kN	Punch NO.;	20
Mean Main Pressure :	32.66	kN	Min :	28.47	kN	Punch NO.;	27
SD :	4.80	%	Max :	35.73	kN	Punch NO.;	20
Filling Depth :	Increase ; 388	Times	Decrease ; 393	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.48	mm	Main Thickness ;	0.78	mm
Filling Depth :	4.17	mm	Current Cam :	Cam B	
Main Air pressure :	0.783	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.21	kN	Max Punch ;	61
Lower Punch :	Average ;	0.41	kN		
	Max ;	1.42	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100524	Tablets			
A.W.C Counter :	1069144	Tablets			
HEP :	125 (0.0%)	Tablets	LEP :	306 (0.0%)	Tablets
GOOD :	1068713 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	06 Hour 00 Min 21 Sec
Total Counter :	1100524	Total Running Time :	2996 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	69	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.22	kN	No		
HEP :	25.0 %	37.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.77	kN	Yes 15	Times	
Ref :		30.17	kN			
LCP :	2.0 %	29.57	kN	Yes 15	Times	
LEP :	25.0 %	22.63	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.12	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.56	kN	Min :	3.21	kN	Punch NO.;	63
		3.90	%	Max :	3.97	kN	Punch NO.;	19
Mean Main Pressure :		29.63	kN	Min :	26.94	kN	Punch NO.;	2
	SD :	3.40	%	Max :	32.82	kN	Punch NO.;	19
Filling Depth :	Increase ;	98	Times	Decrease ;	99	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.48	mm	Main Thickness ;	0.78	mm
Filling Depth :	3.41	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.783	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.21	kN	Max Punch ;	61
Lower Punch :	Average ;	0.41	kN		
	Max ;	1.42	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100524	Tablets			
A.W.C Counter :	1069144	Tablets			
HEP :	125 (0.0%)	Tablets	LEP :	306 (0.0%)	Tablets
GOOD :	1068713 (100.0%)	Tablets			