

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	07 Hour 23 Min 36 Sec
Total Counter :	1375768	Total Running Time :	2997 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.30	kN	No		
HEP :	25.0 %	39.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	32.40	kN	Yes 15	Times	
Ref :		31.77	kN			
LCP :	2.0 %	31.13	kN	Yes 15	Times	
LEP :	25.0 %	23.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.33	kN	Min :	3.79	kN	Punch NO.;	58
SD :	6.10	%	Max :	5.29	kN	Punch NO.;	11
Mean Main Pressure :	31.86	kN	Min :	28.85	kN	Punch NO.;	58
SD :	4.60	%	Max :	35.84	kN	Punch NO.;	11
Filling Depth :	Increase ;	458	Times	Decrease ;	432	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.38	kN	Max Punch ;	12
Lower Punch :	Average ;	0.44	kN		
	Max ;	1.44	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1375768	Tablets			
A.W.C Counter :	1343619	Tablets			
HEP :	171 (0.0%)	Tablets	LEP :	517 (0.0%)	Tablets
GOOD :	1342931 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	07 Hour 23 Min 36 Sec
Total Counter :	1375768	Total Running Time :	2997 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.29	kN	No		
HEP :	25.0 %	35.85	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.26	kN	Yes	15	Times
Ref :		28.68	kN			
LCP :	2.0 %	28.11	kN	Yes	15	Times
LEP :	25.0 %	21.51	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.08	kN	Min :	3.75	kN	Punch NO.;	14
SD :	3.80	%	Max :	4.38	kN	Punch NO.;	56
Mean Main Pressure :	28.44	kN	Min :	25.78	kN	Punch NO.;	71
SD :	3.40	%	Max :	30.55	kN	Punch NO.;	4
Filling Depth :	Increase ;	125	Times	Decrease ;	110	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.50	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.36	kN	Max Punch ;	26
Lower Punch :	Average ;	0.44	kN		
	Max ;	1.44	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1375768	Tablets			
A.W.C Counter :	1343619	Tablets			
HEP :	171 (0.0%)	Tablets	LEP :	517 (0.0%)	Tablets
GOOD :	1342931 (99.9%)	Tablets			