

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	11 Hour 53 Min 08 Sec
Total Counter :	2351252	Total Running Time :	3002 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	84	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.50	kN	No		
HEP :	25.0 %	39.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	32.56	kN	Yes 15	Times	
Ref :		31.92	kN			
LCP :	2.0 %	31.28	kN	Yes 15	Times	
LEP :	25.0 %	23.94	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.08	kN	Min :	3.59	kN	Punch NO.;	17
SD :	5.80	%	Max :	4.80	kN	Punch NO.;	59
Mean Main Pressure :	31.04	kN	Min :	27.90	kN	Punch NO.;	17
SD :	4.80	%	Max :	35.08	kN	Punch NO.;	59
Filling Depth :	Increase ; 705	Times	Decrease ; 630	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.63	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.52	kN	Max Punch ;	19
Lower Punch :	Average ;	0.22	kN		
	Max ;	0.53	kN	Max Punch ;	41
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2351252	Tablets			
A.W.C Counter :	2303146	Tablets			
HEP :	511 (0.0%)	Tablets	LEP :	1235 (0.1%)	Tablets
GOOD :	2301400 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	11 Hour 53 Min 08 Sec
Total Counter :	2351252	Total Running Time :	3002 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.56	kN	No		
HEP :	25.0 %	36.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.47	kN	Yes 15	Times	
Ref :		28.89	kN			
LCP :	2.0 %	28.31	kN	Yes 15	Times	
LEP :	25.0 %	21.67	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.30	kN	Min :	3.92	kN	Punch NO.;	17
SD :	4.40	%	Max :	5.00	kN	Punch NO.;	76
Mean Main Pressure :	29.30	kN	Min :	26.92	kN	Punch NO.;	18
SD :	3.60	%	Max :	32.44	kN	Punch NO.;	76
Filling Depth :	Increase ;	519	Times	Decrease ;	480	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.23	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.52	kN	Max Punch ;	19
Lower Punch :	Average ;	0.22	kN		
	Max ;	0.62	kN	Max Punch ;	68
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2351252	Tablets			
A.W.C Counter :	2303146	Tablets			
HEP :	511 (0.0%)	Tablets	LEP :	1235 (0.1%)	Tablets
GOOD :	2301400 (99.9%)	Tablets			