

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	13 Hour 14 Min 44 Sec
Total Counter :	2651476	Total Running Time :	3003 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	42.65	kN	No		
HEP :	25.0 %	41.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	33.46	kN	Yes 15	Times	
Ref :		32.81	kN			
LCP :	2.0 %	32.15	kN	Yes 15	Times	
LEP :	25.0 %	24.61	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.97	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.05	kN	Min :	3.61	kN	Punch NO.;	45
SD :	5.20	%	Max :	4.80	kN	Punch NO.;	76
Mean Main Pressure :	32.44	kN	Min :	29.62	kN	Punch NO.;	41
SD :	4.10	%	Max :	36.16	kN	Punch NO.;	76
Filling Depth :	Increase ;	794	Times	Decrease ;	749	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.36	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.771	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.54	kN	Max Punch ;	19
Lower Punch :	Average ;	0.46	kN		
	Max ;	0.92	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2651476	Tablets			
A.W.C Counter :	2602225	Tablets			
HEP :	512 (0.0%)	Tablets	LEP :	1393 (0.1%)	Tablets
GOOD :	2600320 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	13 Hour 14 Min 44 Sec
Total Counter :	2651476	Total Running Time :	3003 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.30	kN	No		
HEP :	25.0 %	36.82	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.05	kN	Yes 15	Times	
Ref :		29.46	kN			
LCP :	2.0 %	28.87	kN	Yes 15	Times	
LEP :	25.0 %	22.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.62	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.96	kN	Min :	3.65	kN	Punch NO.;	25
SD :	4.10	%	Max :	4.35	kN	Punch NO.;	46
Mean Main Pressure :	28.91	kN	Min :	27.13	kN	Punch NO.;	41
SD :	3.10	%	Max :	31.47	kN	Punch NO.;	19
Filling Depth :	Increase ;	570	Times	Decrease ;	545	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.72	mm	Current Cam :	Cam B	
Main Air pressure :	0.771	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.42	kN		
	Max ;	0.52	kN	Max Punch ;	19
Lower Punch :	Average ;	0.46	kN		
	Max ;	0.92	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2651476	Tablets			
A.W.C Counter :	2602225	Tablets			
HEP :	512 (0.0%)	Tablets	LEP :	1393 (0.1%)	Tablets
GOOD :	2600320 (99.9%)	Tablets			