

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	11 Hour 21 Min 54 Sec
Total Counter :	2451540	Total Running Time :	3015 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	61	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.60	kN	No		
HEP :	25.0 %	41.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.21	kN	Yes 15	Times	
Ref :		33.54	kN			
LCP :	2.0 %	32.87	kN	Yes 15	Times	
LEP :	25.0 %	25.16	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.48	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.36	kN	Min :	3.65	kN	Punch NO.;	66
SD :	6.30	%	Max :	4.98	kN	Punch NO.;	38
Mean Main Pressure :	33.62	kN	Min :	28.17	kN	Punch NO.;	66
SD :	5.40	%	Max :	37.19	kN	Punch NO.;	7
Filling Depth :	Increase ;	2180	Times	Decrease ;	2126	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.86	mm
Filling Depth :	4.76	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.758	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.51	kN		
	Max ;	0.64	kN	Max Punch ;	35
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.51	kN	Max Punch ;	41
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2451540	Tablets			
A.W.C Counter :	2423153	Tablets			
HEP :	595 (0.0%)	Tablets	LEP :	2464 (0.1%)	Tablets
GOOD :	2420094 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	11 Hour 21 Min 54 Sec
Total Counter :	2451540	Total Running Time :	3015 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.00	kN	No		
HEP :	25.0 %	38.47	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	31.39	kN	Yes	15	Times
Ref :		30.77	kN			
LCP :	2.0 %	30.16	kN	Yes	15	Times
LEP :	25.0 %	23.08	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	21.54	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.31	kN	Min :	3.68	kN	Punch NO.;	37
SD :	5.50	%	Max :	4.84	kN	Punch NO.;	19
Mean Main Pressure :	30.01	kN	Min :	26.80	kN	Punch NO.;	37
SD :	4.30	%	Max :	33.06	kN	Punch NO.;	19
Filling Depth :	Increase ;	1766	Times	Decrease ;	1644	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.39	mm	Current Cam :	Cam B	
Main Air pressure :	0.758	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.51	kN		
	Max ;	0.64	kN	Max Punch ;	27
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.51	kN	Max Punch ;	41
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2451540	Tablets			
A.W.C Counter :	2423153	Tablets			
HEP :	595 (0.0%)	Tablets	LEP :	2464 (0.1%)	Tablets
GOOD :	2420094 (99.9%)	Tablets			