

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510740
Print Interval :	50000 Tablets	Running Time :	00 Hour 27 Min 06 Sec
Total Counter :	100042	Total Running Time :	3029 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	97	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.94	kN	No		
HEP :	25.0 %	42.25	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	34.47	kN	Yes	15	Times
Ref :		33.80	kN			
LCP :	2.0 %	33.12	kN	Yes	15	Times
LEP :	25.0 %	25.35	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	23.66	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.16	kN	Punch NO.;	66
SD :	1.40	%	Max :	2.30	kN	Punch NO.;	1
Mean Main Pressure :	32.97	kN	Min :	27.06	kN	Punch NO.;	27
SD :	4.50	%	Max :	36.01	kN	Punch NO.;	69
Filling Depth :	Increase ;	372	Times	Decrease ;	276	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.90	mm	Current Cam :	Cam B	
Main Air pressure :	0.774	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.24	kN	Max Punch ;	30
Lower Punch :	Average ;	0.27	kN		
	Max ;	0.78	kN	Max Punch ;	65
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100042	Tablets			
A.W.C Counter :	92270	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	11 (0.0%)	Tablets
GOOD :	92258 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510740
Print Interval :	50000 Tablets	Running Time :	00 Hour 27 Min 06 Sec
Total Counter :	100042	Total Running Time :	3029 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	97	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.77	kN	No		
HEP :	25.0 %	38.24	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.20	kN	Yes 15	Times	
Ref :		30.59	kN			
LCP :	2.0 %	29.98	kN	Yes 15	Times	
LEP :	25.0 %	22.94	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.27	kN	Min :	2.20	kN	Punch NO.;	2
SD :	1.30	%	Max :	2.34	kN	Punch NO.;	17
Mean Main Pressure :	30.49	kN	Min :	26.66	kN	Punch NO.;	27
SD :	4.00	%	Max :	33.45	kN	Punch NO.;	43
Filling Depth :	Increase ;	346	Times	Decrease ;	322	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	4.14	mm	Current Cam :	Cam B	
Main Air pressure :	0.774	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.24	kN	Max Punch ;	30
Lower Punch :	Average ;	0.26	kN		
	Max ;	0.76	kN	Max Punch ;	65
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100042	Tablets			
A.W.C Counter :	92270	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	11 (0.0%)	Tablets
GOOD :	92258 (100.0%)	Tablets			