

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510740
Print Interval :	50000 Tablets	Running Time :	12 Hour 19 Min 36 Sec
Total Counter :	2725786	Total Running Time :	3040 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	97	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	44.38	kN	No		
HEP :	25.0 %	42.67	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.82	kN	Yes 15	Times	
Ref :		34.14	kN			
LCP :	2.0 %	33.45	kN	Yes 15	Times	
LEP :	25.0 %	25.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.90	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.34	kN	Min :	2.16	kN	Punch NO.;	23
SD :	4.50	%	Max :	2.59	kN	Punch NO.;	68
Mean Main Pressure :	34.19	kN	Min :	28.32	kN	Punch NO.;	9
SD :	8.90	%	Max :	40.91	kN	Punch NO.;	38
Filling Depth :	Increase ; 565	Times	Decrease ;	430	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.79	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.62	kN	Max Punch ;	63
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.57	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2725786	Tablets			
A.W.C Counter :	2713416	Tablets			
HEP :	44 (0.0%)	Tablets	LEP :	868 (0.0%)	Tablets
GOOD :	2712504 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510740
Print Interval :	50000 Tablets	Running Time :	12 Hour 19 Min 36 Sec
Total Counter :	2725786	Total Running Time :	3040 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	97	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.38	kN	No		
HEP :	25.0 %	38.83	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.68	kN	Yes 15	Times	
Ref :		31.06	kN			
LCP :	2.0 %	30.44	kN	Yes 15	Times	
LEP :	25.0 %	23.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.74	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.39	kN	Min :	2.30	kN	Punch NO.;	39
		2.20	%	Max :	2.65	kN	Punch NO.;	23
Mean Main Pressure :	SD :	31.53	kN	Min :	26.30	kN	Punch NO.;	27
		8.60	%	Max :	41.12	kN	Punch NO.;	70
Filling Depth :	Increase ;	1117	Times	Decrease ;	1055	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	4.42	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.797	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.40	kN	Max Punch ;	3
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.57	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2725786	Tablets			
A.W.C Counter :	2713416	Tablets			
HEP :	44 (0.0%)	Tablets	LEP :	868 (0.0%)	Tablets
GOOD :	2712504 (100.0%)	Tablets			