

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510840
Print Interval :	50000 Tablets	Running Time :	02 Hour 56 Min 29 Sec
Total Counter :	650338	Total Running Time :	3043 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.01	kN	No		
HEP :	25.0 %	41.35	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	33.74	kN	Yes	15	Times
Ref :		33.08	kN			
LCP :	2.0 %	32.42	kN	Yes	15	Times
LEP :	25.0 %	24.81	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	23.16	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.18	kN	Punch NO.;	23
SD :	1.30	%	Max :	2.30	kN	Punch NO.;	29
Mean Main Pressure :	32.92	kN	Min :	28.56	kN	Punch NO.;	27
SD :	4.10	%	Max :	36.31	kN	Punch NO.;	7
Filling Depth :	Increase ;	641	Times	Decrease ;	523	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.749	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.44	kN	Max Punch ;	3
Lower Punch :	Average ;	0.25	kN		
	Max ;	0.62	kN	Max Punch ;	62
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650338	Tablets			
A.W.C Counter :	645582	Tablets			
HEP :	35 (0.0%)	Tablets	LEP :	71 (0.0%)	Tablets
GOOD :	645476 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510840
Print Interval :	50000 Tablets	Running Time :	02 Hour 56 Min 29 Sec
Total Counter :	650338	Total Running Time :	3043 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.18	kN	No		
HEP :	25.0 %	38.64	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.53	kN	Yes 15	Times	
Ref :		30.91	kN			
LCP :	2.0 %	30.29	kN	Yes 15	Times	
LEP :	25.0 %	23.18	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.32	kN	Min :	2.24	kN	Punch NO.;	2
SD :	1.20	%	Max :	2.38	kN	Punch NO.;	25
Mean Main Pressure :	30.54	kN	Min :	26.13	kN	Punch NO.;	27
SD :	4.20	%	Max :	33.09	kN	Punch NO.;	40
Filling Depth :	Increase ;	1349	Times	Decrease ;	1316	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.29	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.749	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.44	kN	Max Punch ;	3
Lower Punch :	Average ;	0.25	kN		
	Max ;	0.61	kN	Max Punch ;	62
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650338	Tablets			
A.W.C Counter :	645582	Tablets			
HEP :	35 (0.0%)	Tablets	LEP :	71 (0.0%)	Tablets
GOOD :	645476 (100.0%)	Tablets			