

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510840
Print Interval :	50000 Tablets	Running Time :	08 Hour 22 Min 23 Sec
Total Counter :	1851190	Total Running Time :	3049 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.63	kN	No		
HEP :	25.0 %	41.95	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.23	kN	Yes 15	Times	
Ref :		33.56	kN			
LCP :	2.0 %	32.89	kN	Yes 15	Times	
LEP :	25.0 %	25.17	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.26	kN	Min :	2.18	kN	Punch NO.;	66
SD :	1.30	%	Max :	2.33	kN	Punch NO.;	29
Mean Main Pressure :	33.61	kN	Min :	29.74	kN	Punch NO.;	47
SD :	5.00	%	Max :	37.14	kN	Punch NO.;	35
Filling Depth :	Increase ;	704	Times	Decrease ;	601	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.741	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.48	kN	Max Punch ;	15
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.46	kN	Max Punch ;	64
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851190	Tablets			
A.W.C Counter :	1844504	Tablets			
HEP :	49 (0.0%)	Tablets	LEP :	744 (0.0%)	Tablets
GOOD :	1843711 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510840
Print Interval :	50000 Tablets	Running Time :	08 Hour 22 Min 23 Sec
Total Counter :	1851190	Total Running Time :	3049 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.46	kN	No		
HEP :	25.0 %	36.98	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.18	kN	Yes 15	Times	
Ref :		29.58	kN			
LCP :	2.0 %	28.99	kN	Yes 15	Times	
LEP :	25.0 %	22.19	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.29	kN	Min :	2.22	kN	Punch NO.;	18
SD :	1.20	%	Max :	2.35	kN	Punch NO.;	45
Mean Main Pressure :	29.02	kN	Min :	23.73	kN	Punch NO.;	27
SD :	4.40	%	Max :	31.63	kN	Punch NO.;	7
Filling Depth :	Increase ;	2033	Times	Decrease ;	2003	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.26	mm	Current Cam :	Cam B	
Main Air pressure :	0.741	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.50	kN	Max Punch ;	15
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.46	kN	Max Punch ;	64
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851190	Tablets			
A.W.C Counter :	1844504	Tablets			
HEP :	49 (0.0%)	Tablets	LEP :	744 (0.0%)	Tablets
GOOD :	1843711 (100.0%)	Tablets			