

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STSH1A00
User ID :	pb97604	Batch NO. :	HAM2501350
Print Interval :	50000 Tablets	Running Time :	06 Hour 18 Min 59 Sec
Total Counter :	600208	Total Running Time :	3059 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	12.75	kN	No		
HEP :	15.0 %	11.92	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	10.52	kN	Yes 15	Times	
Ref :		10.36	kN			
LCP :	1.5 %	10.21	kN	Yes 15	Times	
LEP :	15.0 %	8.81	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.98	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.08	kN	Min :	2.06	kN	Punch NO.;	36
SD :	0.40	%	Max :	2.11	kN	Punch NO.;	26
Mean Main Pressure :	10.46	kN	Min :	9.84	kN	Punch NO.;	33
SD :	3.10	%	Max :	11.17	kN	Punch NO.;	11
Filling Depth :	Increase ;	709	Times	Decrease ;	652	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.65	mm	Main Thickness ;	2.65	mm
Filling Depth :	8.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.685	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	26
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.18	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	600208	Tablets			
A.W.C Counter :	576062	Tablets			
HEP :	2021 (0.4%)	Tablets	LEP :	1366 (0.2%)	Tablets
GOOD :	572675 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STSH1A00
User ID :	pb97604	Batch NO. :	HAM2501350
Print Interval :	50000 Tablets	Running Time :	06 Hour 18 Min 59 Sec
Total Counter :	600208	Total Running Time :	3059 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	12.47	kN	No		
HEP :	15.0 %	11.66	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	10.29	kN	Yes 15	Times	
Ref :		10.14	kN			
LCP :	1.5 %	9.98	kN	Yes 15	Times	
LEP :	15.0 %	8.62	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.13	kN	Min :	2.11	kN	Punch NO.;	3
SD :	0.50	%	Max :	2.15	kN	Punch NO.;	10
Mean Main Pressure :	9.80	kN	Min :	9.04	kN	Punch NO.;	49
SD :	3.90	%	Max :	10.62	kN	Punch NO.;	32
Filling Depth :	Increase ;	692	Times	Decrease ;	727	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.85	mm	Main Thickness ;	2.85	mm
Filling Depth :	8.32	mm	Current Cam :	Cam C	
Main Air pressure :	0.685	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	28
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.18	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	600208	Tablets			
A.W.C Counter :	576062	Tablets			
HEP :	2021 (0.4%)	Tablets	LEP :	1366 (0.2%)	Tablets
GOOD :	572675 (99.4%)	Tablets			