

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo300mg STUB2B00
User ID :	rp98927	Batch NO. :	UBM2502030
Print Interval :	50000 Tablets	Running Time :	01 Hour 34 Min 24 Sec
Total Counter :	200064	Total Running Time :	3113 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	13.32	kN	No		
HEP :	20.0 %	12.99	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	10.99	kN	Yes 15	Times	
Ref :		10.83	kN			
LCP :	1.5 %	10.67	kN	Yes 15	Times	
LEP :	20.0 %	8.66	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	8.34	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.07	kN	Min :	0.97	kN	Punch NO.;	34
SD :	4.70	%	Max :	1.19	kN	Punch NO.;	46
Mean Main Pressure :	10.70	kN	Min :	9.44	kN	Punch NO.;	4
SD :	5.60	%	Max :	12.09	kN	Punch NO.;	6
Filling Depth :	Increase ;	994	Times	Decrease ;	982	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	3.15	mm
Filling Depth :	7.38	mm	Current Cam :	Cam C	
Main Air pressure :	0.763	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200064	Tablets			
A.W.C Counter :	198591	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	198586 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo300mg STUB2B00
User ID :	rp98927	Batch NO. :	UBM2502030
Print Interval :	50000 Tablets	Running Time :	01 Hour 34 Min 24 Sec
Total Counter :	200064	Total Running Time :	3113 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	44	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	11.84	kN	No		
HEP :	20.0 %	11.55	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.77	kN	Yes 15	Times	
Ref :		9.63	kN			
LCP :	1.5 %	9.48	kN	Yes 15	Times	
LEP :	20.0 %	7.70	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.13	kN	Min :	1.04	kN	Punch NO.;	13
SD :	4.30	%	Max :	1.26	kN	Punch NO.;	17
Mean Main Pressure :	9.81	kN	Min :	8.75	kN	Punch NO.;	43
SD :	5.40	%	Max :	11.15	kN	Punch NO.;	25
Filling Depth :	Increase ;	833	Times	Decrease ;	825	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.30	mm	Main Thickness ;	3.30	mm
Filling Depth :	6.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.763	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200064	Tablets			
A.W.C Counter :	198591	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	198586 (100.0%)	Tablets			