

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	rp98927	Batch NO. :	HAM2500975
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 45 Sec
Total Counter :	50018	Total Running Time :	3120 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	199	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.00	kN	No		
HEP :	25.0 %	10.57	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	8.58	kN	Yes 15	Times	
Ref :		8.46	kN			
LCP :	1.5 %	8.33	kN	Yes 15	Times	
LEP :	25.0 %	6.34	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.55	kN	Min :	1.44	kN	Punch NO.;	10
SD :	2.70	%	Max :	1.65	kN	Punch NO.;	5
Mean Main Pressure :	8.56	kN	Min :	7.90	kN	Punch NO.;	10
SD :	2.40	%	Max :	8.92	kN	Punch NO.;	5
Filling Depth :	Increase ;	1401	Times	Decrease ;	1405	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.95	mm	Main Thickness ;	3.95	mm
Filling Depth :	9.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.31	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50018	Tablets			
A.W.C Counter :	43343	Tablets			
HEP :	78 (0.2%)	Tablets	LEP :	17 (0.0%)	Tablets
GOOD :	43248 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	rp98927	Batch NO. :	HAM2500975
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 45 Sec
Total Counter :	50018	Total Running Time :	3120 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	206	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.61	kN	No		
HEP :	25.0 %	11.17	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.07	kN	Yes 15	Times	
Ref :		8.93	kN			
LCP :	1.5 %	8.80	kN	Yes 15	Times	
LEP :	25.0 %	6.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.22	kN	Min :	1.10	kN	Punch NO.;	18
SD :	4.10	%	Max :	1.31	kN	Punch NO.;	46
Mean Main Pressure :	8.41	kN	Min :	7.64	kN	Punch NO.;	18
SD :	2.90	%	Max :	8.89	kN	Punch NO.;	8
Filling Depth :	Increase ;	1073	Times	Decrease ;	1042	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	31	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.05	mm	Pre Thickness ;	5.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.15	mm	Main Thickness ;	4.15	mm
Filling Depth :	10.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.31	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50018	Tablets			
A.W.C Counter :	43343	Tablets			
HEP :	78 (0.2%)	Tablets	LEP :	17 (0.0%)	Tablets
GOOD :	43248 (99.8%)	Tablets			