

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	rp98927	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	01 Hour 05 Min 53 Sec
Total Counter :	250180	Total Running Time :	3141 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.73	kN	No		
HEP :	25.0 %	14.16	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	11.50	kN	Yes 15	Times	
Ref :		11.33	kN			
LCP :	1.5 %	11.16	kN	Yes 15	Times	
LEP :	25.0 %	8.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.47	kN	Punch NO.;	73
SD :	0.80	%	Max :	1.53	kN	Punch NO.;	25
Mean Main Pressure :	11.32	kN	Min :	10.34	kN	Punch NO.;	18
SD :	3.70	%	Max :	12.31	kN	Punch NO.;	62
Filling Depth :	Increase ; 27	Times	Decrease ; 27	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.11	mm
Filling Depth :	5.17	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	67
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250180	Tablets			
A.W.C Counter :	244676	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	244676 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	rp98927	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	01 Hour 05 Min 53 Sec
Total Counter :	250180	Total Running Time :	3141 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	15.94	kN	No		
HEP :	25.0 %	15.33	kN	Yes	10	Rotations 15 Tablets
HCP :	1.5 %	12.45	kN	Yes	15	Times
Ref :		12.26	kN			
LCP :	1.5 %	12.08	kN	Yes	15	Times
LEP :	25.0 %	9.20	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.42	kN	Min :	1.40	kN	Punch NO.;	3
SD :	0.80	%	Max :	1.45	kN	Punch NO.;	62
Mean Main Pressure :	12.39	kN	Min :	11.67	kN	Punch NO.;	35
SD :	2.80	%	Max :	13.21	kN	Punch NO.;	62
Filling Depth :	Increase ;	21	Times	Decrease ;	19	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.14	mm
Filling Depth :	5.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	67
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250180	Tablets			
A.W.C Counter :	244676	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	244676 (100.0%)	Tablets			