

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	02 Hour 44 Min 47 Sec
Total Counter :	650530	Total Running Time :	3142 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	15.72	kN	No		
HEP :	25.0 %	15.12	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	12.28	kN	Yes 15	Times	
Ref :		12.09	kN			
LCP :	1.5 %	11.91	kN	Yes 15	Times	
LEP :	25.0 %	9.07	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.48	kN	Min :	1.45	kN	Punch NO.;	58
SD :	0.80	%	Max :	1.51	kN	Punch NO.;	13
Mean Main Pressure :	12.19	kN	Min :	10.98	kN	Punch NO.;	30
SD :	3.70	%	Max :	13.67	kN	Punch NO.;	39
Filling Depth :	Increase ; 50	Times	Decrease ; 54	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.11	mm
Filling Depth :	5.42	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.768	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	22
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650530	Tablets			
A.W.C Counter :	644734	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	644734 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	02 Hour 44 Min 47 Sec
Total Counter :	650530	Total Running Time :	3142 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.23	kN	No		
HEP :	25.0 %	16.57	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	13.45	kN	Yes 15	Times	
Ref :		13.25	kN			
LCP :	1.5 %	13.05	kN	Yes 15	Times	
LEP :	25.0 %	9.94	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.42	kN	Min :	1.39	kN	Punch NO.;	1
SD :	0.70	%	Max :	1.44	kN	Punch NO.;	52
Mean Main Pressure :	13.29	kN	Min :	12.41	kN	Punch NO.;	20
SD :	3.00	%	Max :	14.72	kN	Punch NO.;	65
Filling Depth :	Increase ;	26	Times	Decrease ;	35	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.14	mm
Filling Depth :	5.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.768	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	22
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650530	Tablets			
A.W.C Counter :	644734	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	644734 (100.0%)	Tablets			