

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	07 Hour 34 Min 07 Sec
Total Counter :	1901408	Total Running Time :	3147 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	16.82	kN	No		
HEP :	25.0 %	16.17	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	13.13	kN	Yes 15	Times	
Ref :		12.94	kN			
LCP :	1.5 %	12.74	kN	Yes 15	Times	
LEP :	25.0 %	9.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.05	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.54	kN	Min :	1.51	kN	Punch NO.;	71
SD :	0.90	%	Max :	1.58	kN	Punch NO.;	20
Mean Main Pressure :	13.05	kN	Min :	11.96	kN	Punch NO.;	20
SD :	3.20	%	Max :	14.11	kN	Punch NO.;	43
Filling Depth :	Increase ; 58	Times	Decrease ;	103	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	5.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.760	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.22	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	69
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1901408	Tablets			
A.W.C Counter :	1895599	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1895599 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	07 Hour 34 Min 07 Sec
Total Counter :	1901408	Total Running Time :	3147 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.65	kN	No		
HEP :	25.0 %	17.93	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	14.56	kN	Yes 15	Times	
Ref :		14.34	kN			
LCP :	1.5 %	14.13	kN	Yes 15	Times	
LEP :	25.0 %	10.76	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.04	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.47	kN	Min :	1.43	kN	Punch NO.;	58
SD :	1.00	%	Max :	1.51	kN	Punch NO.;	29
Mean Main Pressure :	14.51	kN	Min :	13.11	kN	Punch NO.;	20
SD :	3.80	%	Max :	16.25	kN	Punch NO.;	60
Filling Depth :	Increase ;	28	Times	Decrease ;	50	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.11	mm
Filling Depth :	5.58	mm	Current Cam :	Cam B	
Main Air pressure :	0.760	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.22	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	69
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1901408	Tablets			
A.W.C Counter :	1895599	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1895599 (100.0%)	Tablets			