

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503950
Print Interval :	50000 Tablets	Running Time :	07 Hour 08 Min 08 Sec
Total Counter :	1851670	Total Running Time :	3170 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.19	kN	No		
HEP :	25.0 %	17.49	kN	Yes	10	Rotations 15 Tablets
HCP :	1.5 %	14.20	kN	Yes	15	Times
Ref :		13.99	kN			
LCP :	1.5 %	13.78	kN	Yes	15	Times
LEP :	25.0 %	10.50	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.56	kN	Min :	1.53	kN	Punch NO.;	42
SD :	0.90	%	Max :	1.60	kN	Punch NO.;	60
Mean Main Pressure :	14.05	kN	Min :	13.00	kN	Punch NO.;	34
SD :	3.50	%	Max :	15.18	kN	Punch NO.;	71
Filling Depth :	Increase ;	133	Times	Decrease ;	199	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	5.37	mm	Current Cam :	Cam B	
Main Air pressure :	0.777	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.29	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851670	Tablets			
A.W.C Counter :	1846863	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1846863 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503950
Print Interval :	50000 Tablets	Running Time :	07 Hour 08 Min 08 Sec
Total Counter :	1851670	Total Running Time :	3170 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.40	kN	No		
HEP :	25.0 %	17.70	kN	Yes	10	Rotations 15 Tablets
HCP :	1.5 %	14.37	kN	Yes	15	Times
Ref :		14.16	kN			
LCP :	1.5 %	13.94	kN	Yes	15	Times
LEP :	25.0 %	10.62	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.91	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.47	kN	Min :	1.44	kN	Punch NO.;	75
SD :	0.90	%	Max :	1.50	kN	Punch NO.;	61
Mean Main Pressure :	14.25	kN	Min :	12.73	kN	Punch NO.;	6
SD :	4.30	%	Max :	16.14	kN	Punch NO.;	60
Filling Depth :	Increase ;	59	Times	Decrease ;	93	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.15	mm	Main Thickness ;	2.16	mm
Filling Depth :	5.49	mm	Current Cam :	Cam B	
Main Air pressure :	0.777	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.29	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851670	Tablets			
A.W.C Counter :	1846863	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1846863 (100.0%)	Tablets			