

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRALINE 50mg TABS
User ID :	rp98927	Batch NO. :	SED-TAB-XV-25-001A
Print Interval :	50000 Tablets	Running Time :	01 Hour 17 Min 51 Sec
Total Counter :	300190	Total Running Time :	3186 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	16	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.26	kN	No		
HEP :	25.0 %	10.83	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	8.79	kN	Yes 15	Times	
Ref :		8.66	kN			
LCP :	1.5 %	8.53	kN	Yes 15	Times	
LEP :	25.0 %	6.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.07	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.45	kN	Min :	1.42	kN	Punch NO.;	30
SD :	0.70	%	Max :	1.48	kN	Punch NO.;	17
Mean Main Pressure :	8.75	kN	Min :	8.27	kN	Punch NO.;	38
SD :	2.00	%	Max :	9.21	kN	Punch NO.;	59
Filling Depth :	Increase ;	215	Times	Decrease ;	251	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	6.26	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.24	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	65
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300190	Tablets			
A.W.C Counter :	289793	Tablets			
HEP :	0 (0%)	Tablets	LEP :	42 (0.0%)	Tablets
GOOD :	289751 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRALINE 50mg TABS
User ID :	rp98927	Batch NO. :	SED-TAB-XV-25-001A
Print Interval :	50000 Tablets	Running Time :	01 Hour 17 Min 51 Sec
Total Counter :	300190	Total Running Time :	3186 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	17	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	10.70	kN	No		
HEP :	25.0 %	10.29	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	8.35	kN	Yes 15	Times	
Ref :		8.23	kN			
LCP :	1.5 %	8.11	kN	Yes 15	Times	
LEP :	25.0 %	6.17	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.29	kN	Min :	1.25	kN	Punch NO.;	43
SD :	1.30	%	Max :	1.35	kN	Punch NO.;	29
Mean Main Pressure :	8.16	kN	Min :	7.65	kN	Punch NO.;	74
SD :	3.30	%	Max :	9.30	kN	Punch NO.;	62
Filling Depth :	Increase ;	110	Times	Decrease ;	137	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.91	mm
Filling Depth :	5.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.24	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	65
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300190	Tablets			
A.W.C Counter :	289793	Tablets			
HEP :	0 (0%)	Tablets	LEP :	42 (0.0%)	Tablets
GOOD :	289751 (100.0%)	Tablets			