

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRALINE 100mg TABS
User ID :	vg96371	Batch NO. :	SED-TAB-XV-25-001B
Print Interval :	50000 Tablets	Running Time :	01 Hour 05 Min 38 Sec
Total Counter :	250068	Total Running Time :	3189 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.67	kN	No		
HEP :	25.0 %	14.11	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	11.46	kN	Yes 15	Times	
Ref :		11.29	kN			
LCP :	1.5 %	11.12	kN	Yes 15	Times	
LEP :	25.0 %	8.46	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.90	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.47	kN	Min :	1.44	kN	Punch NO.;	28
SD :	0.70	%	Max :	1.49	kN	Punch NO.;	3
Mean Main Pressure :	11.18	kN	Min :	10.87	kN	Punch NO.;	44
SD :	1.40	%	Max :	11.65	kN	Punch NO.;	10
Filling Depth :	Increase ;	232	Times	Decrease ;	268	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.08	mm	Main Thickness ;	3.09	mm
Filling Depth :	7.88	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.741	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	46
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250068	Tablets			
A.W.C Counter :	239102	Tablets			
HEP :	0 (0%)	Tablets	LEP :	42 (0.0%)	Tablets
GOOD :	239060 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRALINE 100mg TABS
User ID :	vg96371	Batch NO. :	SED-TAB-XV-25-001B
Print Interval :	50000 Tablets	Running Time :	01 Hour 05 Min 38 Sec
Total Counter :	250068	Total Running Time :	3189 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	15.89	kN	No		
HEP :	25.0 %	15.28	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	12.41	kN	Yes 15	Times	
Ref :		12.23	kN			
LCP :	1.5 %	12.04	kN	Yes 15	Times	
LEP :	25.0 %	9.17	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.37	kN	Min :	1.32	kN	Punch NO.;	72
		1.80	%	Max :	1.42	kN	Punch NO.;	57
Mean Main Pressure :		12.28	kN	Min :	11.68	kN	Punch NO.;	29
	SD :	2.50	%	Max :	13.13	kN	Punch NO.;	68
Filling Depth :	Increase ;	133	Times	Decrease ;	147	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.23	mm	Main Thickness ;	3.24	mm
Filling Depth :	7.65	mm	Current Cam :	Cam B	
Main Air pressure :	0.741	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	31
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250068	Tablets			
A.W.C Counter :	239102	Tablets			
HEP :	0 (0%)	Tablets	LEP :	42 (0.0%)	Tablets
GOOD :	239060 (100.0%)	Tablets			