

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIU1B00
User ID :	rp98927	Batch NO. :	IUM2501240
Print Interval :	50000 Tablets	Running Time :	02 Hour 39 Min 31 Sec
Total Counter :	300086	Total Running Time :	3193 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.1	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.17	kN	No		
HEP :	24.0 %	24.00	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	19.74	kN	Yes 20	Times	
Ref :		19.36	kN			
LCP :	2.0 %	18.97	kN	Yes 20	Times	
LEP :	24.0 %	14.71	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.55	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.58	kN	Min :	2.45	kN	Punch NO.;	7
SD :	2.20	%	Max :	2.74	kN	Punch NO.;	25
Mean Main Pressure :	18.90	kN	Min :	16.94	kN	Punch NO.;	10
SD :	5.00	%	Max :	22.86	kN	Punch NO.;	25
Filling Depth :	Increase ; 55	Times	Decrease ; 37	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	6.90	mm	Current Cam :	Cam C	
Main Air pressure :	0.777	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	37
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.34	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300086	Tablets			
A.W.C Counter :	294635	Tablets			
HEP :	646 (0.2%)	Tablets	LEP :	63 (0.0%)	Tablets
GOOD :	293926 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIU1B00
User ID :	rp98927	Batch NO. :	IUM2501240
Print Interval :	50000 Tablets	Running Time :	02 Hour 39 Min 31 Sec
Total Counter :	300086	Total Running Time :	3193 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.1	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.96	kN	No		
HEP :	24.0 %	19.99	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.44	kN	Yes 20	Times	
Ref :		16.12	kN			
LCP :	2.0 %	15.80	kN	Yes 20	Times	
LEP :	24.0 %	12.25	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.36	kN	Min :	2.25	kN	Punch NO.;	1
SD :	2.50	%	Max :	2.56	kN	Punch NO.;	25
Mean Main Pressure :	16.30	kN	Min :	14.86	kN	Punch NO.;	52
SD :	5.50	%	Max :	19.89	kN	Punch NO.;	25
Filling Depth :	Increase ; 81	Times	Decrease ; 53	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.91	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.777	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	37
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.34	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300086	Tablets			
A.W.C Counter :	294635	Tablets			
HEP :	646 (0.2%)	Tablets	LEP :	63 (0.0%)	Tablets
GOOD :	293926 (99.8%)	Tablets			