

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	pb97604	Batch NO. :	EGM2500110
Print Interval :	50000 Tablets	Running Time :	17 Hour 49 Min 23 Sec
Total Counter :	36648	Total Running Time :	3209 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.81	kN	No		
HEP :	20.0 %	8.46	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.19	kN	Yes 15	Times	
Ref :		7.05	kN			
LCP :	2.0 %	6.91	kN	Yes 15	Times	
LEP :	20.0 %	5.64	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.67	kN	Min :	1.65	kN	Punch NO.;	26
SD :	0.40	%	Max :	1.69	kN	Punch NO.;	56
Mean Main Pressure :	7.12	kN	Min :	6.75	kN	Punch NO.;	63
SD :	1.90	%	Max :	7.43	kN	Punch NO.;	40
Filling Depth :	Increase ;	2	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.62	mm	Main Thickness ;	2.62	mm
Filling Depth :	4.57	mm	Current Cam :	Cam B	
Main Air pressure :	0.753	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	60
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	36648	Tablets			
A.W.C Counter :	28444	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	28444 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	pb97604	Batch NO. :	EGM2500110
Print Interval :	50000 Tablets	Running Time :	17 Hour 49 Min 23 Sec
Total Counter :	36648	Total Running Time :	3209 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.65	kN	No		
HEP :	20.0 %	8.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.06	kN	Yes 15	Times	
Ref :		6.92	kN			
LCP :	2.0 %	6.78	kN	Yes 15	Times	
LEP :	20.0 %	5.54	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.19	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.58	kN	Min :	1.54	kN	Punch NO.;	57
SD :	0.80	%	Max :	1.61	kN	Punch NO.;	4
Mean Main Pressure :	6.91	kN	Min :	6.37	kN	Punch NO.;	45
SD :	3.70	%	Max :	7.53	kN	Punch NO.;	24
Filling Depth :	Increase ;	0	Times	Decrease ;	4	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.78	mm
Filling Depth :	4.51	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	60
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	36648	Tablets			
A.W.C Counter :	28444	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	28444 (100.0%)	Tablets			