

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	am98755	Batch NO. :	EGM2500210
Print Interval :	50000 Tablets	Running Time :	05 Hour 19 Min 33 Sec
Total Counter :	714832	Total Running Time :	3221 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	41	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.60	kN	No		
HEP :	20.0 %	9.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.83	kN	Yes 15	Times	
Ref :		7.68	kN			
LCP :	2.0 %	7.52	kN	Yes 15	Times	
LEP :	20.0 %	6.14	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.57	kN	Min :	1.53	kN	Punch NO.;	32
SD :	0.80	%	Max :	1.60	kN	Punch NO.;	29
Mean Main Pressure :	7.65	kN	Min :	6.79	kN	Punch NO.;	13
SD :	2.90	%	Max :	8.14	kN	Punch NO.;	25
Filling Depth :	Increase ; 19	Times	Decrease ;	19	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	124800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	2.59	mm
Filling Depth :	4.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.763	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	43
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.40	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	714832	Tablets			
A.W.C Counter :	701964	Tablets			
HEP :	138 (0.0%)	Tablets	LEP :	390 (0.1%)	Tablets
GOOD :	701436 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	am98755	Batch NO. :	EGM2500210
Print Interval :	50000 Tablets	Running Time :	05 Hour 19 Min 33 Sec
Total Counter :	714832	Total Running Time :	3221 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.79	kN	No		
HEP :	20.0 %	8.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.17	kN	Yes 15	Times	
Ref :		7.03	kN			
LCP :	2.0 %	6.89	kN	Yes 15	Times	
LEP :	20.0 %	5.62	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.41	kN	Punch NO.;	31
SD :	1.10	%	Max :	1.50	kN	Punch NO.;	19
Mean Main Pressure :	7.05	kN	Min :	6.62	kN	Punch NO.;	13
SD :	2.40	%	Max :	7.43	kN	Punch NO.;	7
Filling Depth :	Increase ;	21	Times	Decrease ;	21	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	124800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	4.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.763	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	43
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.41	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	714832	Tablets			
A.W.C Counter :	701964	Tablets			
HEP :	138 (0.0%)	Tablets	LEP :	390 (0.1%)	Tablets
GOOD :	701436 (99.9%)	Tablets			