

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	sj97904	Batch NO. :	EGM2500310
Print Interval :	50000 Tablets	Running Time :	07 Hour 02 Min 59 Sec
Total Counter :	930216	Total Running Time :	3230 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.60	kN	No		
HEP :	20.0 %	9.22	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	7.83	kN	Yes	15	Times
Ref :		7.68	kN			
LCP :	2.0 %	7.53	kN	Yes	15	Times
LEP :	20.0 %	6.14	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	5.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.50	kN	Min :	1.44	kN	Punch NO.;	31
SD :	1.50	%	Max :	1.55	kN	Punch NO.;	3
Mean Main Pressure :	7.28	kN	Min :	4.80	kN	Punch NO.;	44
SD :	10.30	%	Max :	8.44	kN	Punch NO.;	63
Filling Depth :	Increase ;	49	Times	Decrease ;	77	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	2.59	mm
Filling Depth :	4.50	mm	Current Cam :	Cam B	
Main Air pressure :	0.208	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	43	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	64
Lower Punch :	Average ;	0.23	kN		
	Max ;	0.49	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	930216	Tablets			
A.W.C Counter :	915537	Tablets			
HEP :	386 (0.0%)	Tablets	LEP :	827 (0.1%)	Tablets
GOOD :	914324 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	sj97904	Batch NO. :	EGM2500310
Print Interval :	50000 Tablets	Running Time :	07 Hour 02 Min 59 Sec
Total Counter :	930216	Total Running Time :	3230 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.98	kN	No		
HEP :	20.0 %	8.62	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	7.33	kN	Yes	15	Times
Ref :		7.19	kN			
LCP :	2.0 %	7.04	kN	Yes	15	Times
LEP :	20.0 %	5.75	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	5.39	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.42	kN	Min :	1.35	kN	Punch NO.;	31
SD :	2.00	%	Max :	1.47	kN	Punch NO.;	33
Mean Main Pressure :	7.04	kN	Min :	6.34	kN	Punch NO.;	64
SD :	3.40	%	Max :	7.78	kN	Punch NO.;	6
Filling Depth :	Increase ;	71	Times	Decrease ;	80	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	4.60	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.208	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	43	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	64
Lower Punch :	Average ;	0.29	kN		
	Max ;	0.53	kN	Max Punch ;	30
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	930216	Tablets			
A.W.C Counter :	915537	Tablets			
HEP :	386 (0.0%)	Tablets	LEP :	827 (0.1%)	Tablets
GOOD :	914324 (99.9%)	Tablets			