

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	sj97904	Batch NO. :	JBM2503540
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 49 Sec
Total Counter :	50014	Total Running Time :	3231 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	140	%	Manual ;	27	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.31	kN	No		
HEP :	20.0 %	12.29	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.45	kN	Yes	15	Times
Ref :		10.24	kN			
LCP :	2.0 %	10.04	kN	Yes	15	Times
LEP :	20.0 %	8.19	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.93	kN	Min :	1.87	kN	Punch NO.;	50
SD :	1.70	%	Max :	2.03	kN	Punch NO.;	12
Mean Main Pressure :	10.25	kN	Min :	9.48	kN	Punch NO.;	17
SD :	3.50	%	Max :	10.94	kN	Punch NO.;	2
Filling Depth :	Increase ;	25	Times	Decrease ;	34	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.70	mm	Main Thickness ;	3.70	mm
Filling Depth :	12.22	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.747	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	40
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50014	Tablets			
A.W.C Counter :	38924	Tablets			
HEP :	58 (0.1%)	Tablets	LEP :	90 (0.2%)	Tablets
GOOD :	38776 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	sj97904	Batch NO. :	JBM2503540
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 49 Sec
Total Counter :	50014	Total Running Time :	3231 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	140	%	Manual ;	40	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.54	kN	No		
HEP :	20.0 %	11.57	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.84	kN	Yes	15	Times
Ref :		9.64	kN			
LCP :	2.0 %	9.45	kN	Yes	15	Times
LEP :	20.0 %	7.71	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.75	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.74	kN	Punch NO.;	46
SD :	1.10	%	Max :	1.82	kN	Punch NO.;	53
Mean Main Pressure :	9.34	kN	Min :	8.66	kN	Punch NO.;	22
SD :	2.40	%	Max :	9.84	kN	Punch NO.;	8
Filling Depth :	Increase ;	10	Times	Decrease ;	7	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.90	mm	Main Thickness ;	3.90	mm
Filling Depth :	12.54	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.747	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	46
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50014	Tablets			
A.W.C Counter :	38924	Tablets			
HEP :	58 (0.1%)	Tablets	LEP :	90 (0.2%)	Tablets
GOOD :	38776 (99.6%)	Tablets			