

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	sj97904	Batch NO. :	JBM2503540
Print Interval :	50000 Tablets	Running Time :	03 Hour 45 Min 20 Sec
Total Counter :	450168	Total Running Time :	3234 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	27	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	12.94	kN	No		
HEP :	20.0 %	12.43	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.56	kN	Yes	15	Times
Ref :		10.36	kN			
LCP :	2.0 %	10.15	kN	Yes	15	Times
LEP :	20.0 %	8.28	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	7.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.84	kN	Punch NO.;	29
SD :	1.50	%	Max :	1.98	kN	Punch NO.;	12
Mean Main Pressure :	10.27	kN	Min :	9.31	kN	Punch NO.;	51
SD :	3.20	%	Max :	10.86	kN	Punch NO.;	6
Filling Depth :	Increase ;	62	Times	Decrease ;	87	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.70	mm	Main Thickness ;	3.70	mm
				Cam D	
Filling Depth :	13.15	mm	Current Cam :	12.5-	
				18mm	
Main Air pressure :	0.761	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	44
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450168	Tablets			
A.W.C Counter :	434942	Tablets			
HEP :	112 (0.0%)	Tablets	LEP :	226 (0.1%)	Tablets
GOOD :	434604 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	sj97904	Batch NO. :	JBM2503540
Print Interval :	50000 Tablets	Running Time :	03 Hour 45 Min 20 Sec
Total Counter :	450168	Total Running Time :	3234 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	40	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	12.43	kN	No		
HEP :	20.0 %	11.93	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.14	kN	Yes	15	Times
Ref :		9.94	kN			
LCP :	2.0 %	9.74	kN	Yes	15	Times
LEP :	20.0 %	7.95	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	7.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.79	kN	Min :	1.70	kN	Punch NO.;	24
SD :	1.70	%	Max :	1.86	kN	Punch NO.;	12
Mean Main Pressure :	9.81	kN	Min :	9.29	kN	Punch NO.;	51
SD :	2.70	%	Max :	10.44	kN	Punch NO.;	15
Filling Depth :	Increase ;	109	Times	Decrease ;	89	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.90	mm	Main Thickness ;	3.90	mm
Filling Depth :	13.79	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.761	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	44
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450168	Tablets			
A.W.C Counter :	434942	Tablets			
HEP :	112 (0.0%)	Tablets	LEP :	226 (0.1%)	Tablets
GOOD :	434604 (99.9%)	Tablets			