

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	sj97904	Batch NO. :	JBM2502480
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 35 Sec
Total Counter :	301490	Total Running Time :	3271 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	330	%	Manual ;	27	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	19.50	kN	No		
HEP :	25.0 %	18.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.30	kN	Yes 15	Times	
Ref :		15.00	kN			
LCP :	2.0 %	14.70	kN	Yes 15	Times	
LEP :	25.0 %	11.25	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.50	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.82	kN	Min :	2.68	kN	Punch NO.;	52
SD :	2.90	%	Max :	3.00	kN	Punch NO.;	6
Mean Main Pressure :	15.43	kN	Min :	14.18	kN	Punch NO.;	52
SD :	4.10	%	Max :	16.93	kN	Punch NO.;	43
Filling Depth :	Increase ; 61	Times	Decrease ; 74	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	56	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.30	mm	Main Thickness ;	4.30	mm
Filling Depth :	17.40	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	301490	Tablets			
A.W.C Counter :	290616	Tablets			
HEP :	32 (0.0%)	Tablets	LEP :	63 (0.0%)	Tablets
GOOD :	290521 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	sj97904	Batch NO. :	JBM2502480
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 35 Sec
Total Counter :	301490	Total Running Time :	3271 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	321	%	Manual ;	40	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.92	kN	No		
HEP :	25.0 %	17.23	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.06	kN	Yes	15	Times
Ref :		13.79	kN			
LCP :	2.0 %	13.51	kN	Yes	15	Times
LEP :	25.0 %	10.34	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.83	kN	Min :	2.69	kN	Punch NO.;	41
SD :	2.70	%	Max :	3.03	kN	Punch NO.;	43
Mean Main Pressure :	13.88	kN	Min :	12.86	kN	Punch NO.;	37
SD :	3.60	%	Max :	15.29	kN	Punch NO.;	43
Filling Depth :	Increase ;	43	Times	Decrease ;	57	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	55	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.50	mm	Main Thickness ;	4.50	mm
Filling Depth :	16.13	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	301490	Tablets			
A.W.C Counter :	290616	Tablets			
HEP :	32 (0.0%)	Tablets	LEP :	63 (0.0%)	Tablets
GOOD :	290521 (100.0%)	Tablets			