

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	pb97604	Batch NO. :	JBM2502580
Print Interval :	50000 Tablets	Running Time :	03 Hour 20 Min 19 Sec
Total Counter :	350096	Total Running Time :	3279 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	350	%	Manual ;	160	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.58	kN	No		
HEP :	25.0 %	17.86	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.58	kN	Yes 15	Times	
Ref :		14.29	kN			
LCP :	2.0 %	14.01	kN	Yes 15	Times	
LEP :	25.0 %	10.72	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.00	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.87	kN	Min :	2.67	kN	Punch NO.;	31
SD :	3.30	%	Max :	3.10	kN	Punch NO.;	6
Mean Main Pressure :	14.36	kN	Min :	12.93	kN	Punch NO.;	25
SD :	4.60	%	Max :	15.90	kN	Punch NO.;	32
Filling Depth :	Increase ;	374	Times	Decrease ;	312	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	60	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.40	mm	Main Thickness ;	4.40	mm
Filling Depth :	16.50	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.676	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	25	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.17	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350096	Tablets			
A.W.C Counter :	343493	Tablets			
HEP :	420 (0.1%)	Tablets	LEP :	72 (0.0%)	Tablets
GOOD :	343001 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	pb97604	Batch NO. :	JBM2502580
Print Interval :	50000 Tablets	Running Time :	03 Hour 20 Min 19 Sec
Total Counter :	350096	Total Running Time :	3279 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	350	%	Manual ;	150	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.47	kN	No		
HEP :	25.0 %	16.80	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.71	kN	Yes 15	Times	
Ref :		13.44	kN			
LCP :	2.0 %	13.17	kN	Yes 15	Times	
LEP :	25.0 %	10.08	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.80	kN	Min :	2.56	kN	Punch NO.;	37
SD :	2.90	%	Max :	3.03	kN	Punch NO.;	29
Mean Main Pressure :	13.50	kN	Min :	11.94	kN	Punch NO.;	37
SD :	3.60	%	Max :	14.38	kN	Punch NO.;	6
Filling Depth :	Increase ;	170	Times	Decrease ;	193	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	60	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.99	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.55	mm	Main Thickness ;	4.55	mm
				Cam E	
Filling Depth :	15.69	mm	Current Cam :	16.5-	
				22mm	
Main Air pressure :	0.676	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	25	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.17	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350096	Tablets			
A.W.C Counter :	343546	Tablets			
HEP :	420 (0.1%)	Tablets	LEP :	72 (0.0%)	Tablets
GOOD :	343054 (99.9%)	Tablets			